## VOLVO WHEELED LOADERS L L20F VOLVO D3.6D STAGE IIIA/TIER 3 (2010-2013)



<b>ENGINE</b> Volvo D3.6D Capacity: 10,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra FE 5W-30	Agrisynth LSP Ultra 10W-40	Agrisynth LSP 10W-40

Check every 8 hours, change every 1000 hours

DIFFERENTIAL FRONT Capacity: 4,1 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Change every 1500 hours	'	

DIFFERENTIAL FRONT LIMITED SLIP Capacity: 4,1 liter		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
Change every 1500 hours	<u>'</u>	

TRANSAXLE REAR Capacity: 5,8 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Change every 1500 hours		,

TRANSAXLE REAR WITH LIMITED SLIP DIFFERENTIAL Capacity: 5,8 liter		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
Change every 1500 hours		

## VOLVO WHEELED LOADERS L L20F VOLVO D3.6D STAGE IIIA/TIER 3 (2010-2013)



HYDRAULIC SYSTEM		
Capacity: 60 liter		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Perlus H 68		
Change every 1500 hours		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 46	Perlus H 32	
Change every 1500 hours		
USE		CLIMATE
Alternative (acceptable)		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		
Change every 1500 hours		
USE		CLIMATE
Alternative (acceptable)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40
Change every 1500 hours		
USE		CLIMATE
Biodegradable oil		Moderate
PRODUCT RECOMMENDATION 1		
Perlus Biosynth 46		
Change every 1500 hours		

HYDRAULIC BRAKE SYSTEM Capacity: 1 liter		
use Normal		CLIMATE  Moderate
PRODUCT RECOMMENDATION 1 Agrisynth LSP Ultra FE 5W-30	PRODUCT RECOMMENDATION 2 Agrisynth LSP Ultra 10W-40	PRODUCT RECOMMENDATION 3 Agrisynth LSP 10W-40

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.