

VOLVO WHEELED LOADERS L L45F (2009-2011)



ENGINE Volvo D5D CAE3 Stage IIIA/Tier 3
Capacity: 16 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Agrisynth LSP Ultra FE 5W-30

PRODUCT RECOMMENDATION 2

Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 3

Armado Synth LSP Ultra 5W-30

Check every 8 hours, change every 500 hours

DIFFERENTIAL FRONT

Capacity: 17,5 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90

Change every 1000 hours

DIFFERENTIAL REAR

Capacity: 18,7 liter (+ Transferbox)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90

Change every 1000 hours

TRANSFERBOX

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90

Change every 1000 hours

VOLVO WHEELED LOADERS L L45F (2009-2011)



HYDRAULIC SYSTEM

Capacity: 95 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	Multifleet SCD 30

Change every 1500 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	Perlus Biosynth 32	Perlus H 32

Change every 1500 hours

USE		CLIMATE
Biodegradable oil		Mediterranean
PRODUCT RECOMMENDATION 1		
Perlus Biosynth 46		

Change every 1500 hours

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

COOLING SYSTEM

Capacity: 20 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	

Check every 8 hours, change every 6000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.