

VOLVO WHEELED LOADERS L L60F (2007-2012)



ENGINE Volvo D6E LCE3
Capacity: 20 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra FE 5W-30	Agrisynth LSP Ultra 10W-40	Agrisynth LSP 10W-40

Check every 8 hours, change every 500 hours

DIFFERENTIAL FRONT
Capacity: 24 liter

USE	CLIMATE
Extended	Moderate

PRODUCT RECOMMENDATION 1		
Agrifluid Synth XHP Ultra		

Change every 2000 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrifluid HT-Plus	Agrifluid HT	

Change every 1000 hours

DIFFERENTIAL REAR
Capacity: 24 liter

USE	CLIMATE
Extended	Moderate

PRODUCT RECOMMENDATION 1		
Agrifluid Synth XHP Ultra		

Change every 2000 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrifluid HT-Plus	Agrifluid HT	

Change every 1000 hours

VOLVO WHEELED LOADERS L L60F (2007-2012)



HUB REDUCTIONS FRONT

USE	CLIMATE
Extended	Moderate

PRODUCT RECOMMENDATION 1

Agrifluid Synth XHP Ultra*Change every 2000 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Agrifluid HT-Plus

PRODUCT RECOMMENDATION 2

Agrifluid HT*Change every 1000 hours*

HUB REDUCTIONS REAR

USE	CLIMATE
Extended	Moderate

PRODUCT RECOMMENDATION 1

Agrifluid Synth XHP Ultra*Change every 2000 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Agrifluid HT-Plus

PRODUCT RECOMMENDATION 2

Agrifluid HT*Change every 1000 hours*

TRANSMISSION Volvo HTE 110

Capacity: 20 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2032

PRODUCT RECOMMENDATION 2

ATF Almirol*Change every 2000 hours*

HYDRAULIC SYSTEM

Capacity: 90 liter (Tank)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Perlus H 46

PRODUCT RECOMMENDATION 2

Perlus H 68*Change every 4000 hours*

VOLVO WHEELED LOADERS L L60F (2007-2012)



GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
HT Q9 High Grade Grease	Labora Grease	Q5 MP Calcep Grease EP 2

COOLING SYSTEM

Capacity: 30 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	

Change every 48 months/ 6000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.