## **VOLVO WHEELED LOADERS L L90F** (2007-2011)



<b>ENGINE</b> Volvo D6E LAE3 Capacity: 20 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra FE 5W-30	Agrisynth LSP Ultra 10W-40	Agrisynth LSP 10W-40

Change every 600 hours

DIFFERENTIAL FRONT Capacity: 35 liter	
USE	CLIMATE
Extended	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid Synth XHP Ultra	
Change every 2000 hours	

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrifluid HT-Plus	Agrifluid HT	
Champio avera 1000 havera		5

Change every 1000 hours

DIFFERENTIAL REAR Capacity: 27 liter	
USE	CLIMATE
Extended	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid Synth XHP Ultra	

Change every 2000 hours

use Normal		climate Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrifluid HT-Plus	Agrifluid HT	
Ohamma 4000 haven		

Change every 1000 hours

## **VOLVO WHEELED LOADERS L L90F** (2007-2011)



HUB REDUCTIONS FRONT		
USE		CLIMATE
Extended		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid Synth XHP Ultra		
Change every 2000 hours		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrifluid HT-Plus	Agrifluid HT	
Change every 1000 hours		

HUB REDUCTIONS REAR	
USE	CLIMATE
Extended	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid Synth XHP Ultra	
	1

Change every 2000 hours

use Normal		climate Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrifluid HT-Plus	Agrifluid HT	
<u>.</u>		

Change every 1000 hours

TRANSMISSION Volvo HTE 125 Capacity: 21 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	

Change every 2000 hours

HYDRAULIC SYSTEM Capacity: 90 liter (Tank)		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 46	Perlus H 68	
Change every 4000 hours		·

## **VOLVO WHEELED LOADERS L L90F** (2007-2011)



GREASE POINTS/NIPPLES			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
HT Q9 High Grade Grease	Labora Grease	Q5 MP Calcep Grease EP 2	

COOLING SYSTEM Capacity: 30 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant SP 15+	Coolant SP 12		
Change every 48 months/ 6000 hou	rs		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.