

VOLVO ARTICULATED HAULERS A/T A40G FS (6X6) VOLVO D16J (TIER 4F / STAGE IV) (2015 AND AFTER)



ENGINE Volvo D16J (Tier 4f / Stage IV)
Capacity: 54 liter

USE

Normal, fuel sulfur level < 15 ppm

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Agridiesel MSP 15W-40

PRODUCT RECOMMENDATION 2

Dieselfleet MSP 10W-30

PRODUCT RECOMMENDATION 3

Dieselfleet MSP 15W-40

Check every 8 hours, change every 500 hours

DIFFERENTIAL FRONT

Capacity: 26 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

DIFFERENTIAL REAR LEADING + TRAILING

Capacity: 56 liter (Total)

We are unable to give a standard recommendation for this component. Please contact our service department.

TRANSFERBOX Volvo IL2

Capacity: 9 liter (Dry fill), Capacity: 8 liter (Service fill)

We are unable to give a standard recommendation for this component. Please contact our service department.

TRANSMISSION Volvo PT 2519 9/3

Capacity: 43 liter

USE

Alternative (acceptable)

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2032

PRODUCT RECOMMENDATION 2

ATF Almirol

Change every 1000 hours

VOLVO ARTICULATED HAULERS A/T A40G FS (6X6) VOLVO D16J (TIER 4F / STAGE IV) (2015 AND AFTER)

**HYDRAULIC SYSTEM**

Capacity: 245 liter (Hydraulic system including tank), Capacity: 191 liter (Hydraulic tank)

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 46	Perlus H 68	

Change every 4000 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 32		

Change every 4000 hours

USE		CLIMATE
Biodegradable oil		Moderate
PRODUCT RECOMMENDATION 1		
Perlus Biosynth 46		

*Change every 4000 hours***GREASE POINTS/NIPPLES GENERAL**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

GREASE POINTS/NIPPLES HITCH JOINT

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
HT Q9 High Grade Grease	Labora Grease	

VOLVO ARTICULATED HAULERS A/T A40G FS (6X6) VOLVO D16J (TIER 4F / STAGE IV) (2015 AND AFTER)



COOLING CIRCUIT FOR BRAKES

Capacity: 226 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Agrifluid Synth XHP Ultra

Change every 4000 hours

USE	CLIMATE
Alternative (acceptable)	Moderate

PRODUCT RECOMMENDATION 1

Agrifluid HT-Plus

PRODUCT RECOMMENDATION 2

Agrifluid HT

Change every 2000 hours

COOLING SYSTEM

Capacity: 75 liter (Dry fill), Capacity: 51 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 15+

PRODUCT RECOMMENDATION 2

Coolant SP 12

Change every 48 months/ 6000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.