VOLVO MOTOR GRADERS G G710 (2001-2002)



	CLIMATE
	Moderate
PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40

Change every 250 hours

DIFFERENTIALS TANDEMS Capacity: 100 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrifluid HT-Plus	Agrifluid HT	

Change every 1500 hours

TRANSMISSION Capacity: 38 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Armado Synth 5W-30	Multifleet SHPD 15W-40	

Change every 1000 hours

HYDRAULIC SYSTEM Capacity: 180 liter, Capacity: 80 liter (AW	D)	
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 46	Perlus H 68	
Change every 2000 hours		

 GREASE POINTS/NIPPLES

 LIMATE

 USE
 CLIMATE

 Normal
 PRODUCT RECOMMENDATION 1
 PRODUCT RECOMMENDATION 2
 PRODUCT RECOMMENDATION 3

 Labora Grease
 Q5 MP Calcep Grease EP 2
 MP Lithep Grease EP 2

VOLVO MOTOR GRADERS G G710 (2001-2002)



COOLING SYSTEM Capacity: 45 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	

Change every 2000 hours

FINAL DRIVE GEARBOX Capacity: 34 liter (double reduction), Capac	city: 23 liter (single reduction)	
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gearlube HS GL-5 80W-140		
		5

Change every 1000 hours

use Normal		climate Moderate
PRODUCT RECOMMENDATION 1 Gearlube GL-5 80W-90	PRODUCT RECOMMENDATION 2 Unigear HS GL-3/GL-5 80W-90	

Change every 1000 hours

PUMP DRIVE GEARBOX Capacity: 3 liter	
USE	CLIMATE
Normal	Mediterranean
PRODUCT RECOMMENDATION 1	
Gearlube HS GL-5 80W-140	

Change every 1000 hours

	CLIMATE
	Moderate
PRODUCT RECOMMENDATION 2	
Unigear HS GL-3/GL-5 80W-90	

Change every 1000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.