

VOLVO BACKHOE LOADERS BL BL71B (2011-2015)



ENGINE Volvo D5D CAE3 Stage IIIA/Tier 3
Capacity: 14-15 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra FE 5W-30	Agrisynth LSP Ultra 10W-40	Agrisynth LSP 10W-40

Check every 8 hours, change every 500 hours

DIFFERENTIAL FRONT
Capacity: 6,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrifluid HT-Plus	Agrifluid HT	

Change every 1000 hours

DIFFERENTIAL REAR
Capacity: 14,5 liter (+ hub reductions)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrifluid HT-Plus	Agrifluid HT	

Change every 1000 hours

HUB REDUCTIONS FRONT
Capacity: 0,8 liter (each hub)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrifluid HT-Plus	Agrifluid HT	

Change every 1000 hours

HUB REDUCTIONS REAR

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrifluid HT-Plus	Agrifluid HT	

Change every 1000 hours

VOLVO BACKHOE LOADERS BL BL71B (2011-2015)



TRANSMISSION Powershift 4/4
Capacity: 14-16 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrifluid HT-Plus	Agrifluid HT	

Change every 2000 hours

TRANSMISSION PowerShuttle 4/4
Capacity: 14-16 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrifluid HT-Plus	Agrifluid HT	

Change every 2000 hours

HYDRAULIC SYSTEM
Capacity: 39 liter (Hydraulic tank)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1		
Perlus H 68		

Check every 8 hours, change every 1000 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 46	Perlus H 32	

Check every 8 hours, change every 1000 hours

COOLING SYSTEM
Capacity: 22 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	

Check every 8 hours, change every 6000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.