PRODUCT RECOMMENDATION

# WACKER NEUSON TRACKED EXCAVATORS 3703 YANMAR 4TNE88-ENSR (AD00001->)

**ENGINE** Yanmar 4TNE88-ENSR
Capacity: 7,5 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Tropical |
| PRODUCT RECOMMENDATION 1 | | |
| **Multifleet SCD 40** | | |

*Change every 500 hours*

| USE | | CLIMATE |
|---|---|---|
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| **Multifleet SCD 30** | | |

*Change every 500 hours*

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| **Agrisynth LSP Ultra FE 5W-30** | **Agrisynth LSP 10W-40** | **Kroontrak CVT 10W-40** |

*Change every 500 hours*

| USE | | CLIMATE |
|---|---|---|
| Normal | | Cold |
| PRODUCT RECOMMENDATION 1 | | |
| **Multifleet SCD 10W** | | |

*Change every 500 hours*

| USE | | CLIMATE |
|---|---|---|
| Initial service | | Tropical |
| PRODUCT RECOMMENDATION 1 | | |
| **Multifleet SCD 40** | | |

*Change every 50 hours*

| USE | | CLIMATE |
|---|---|---|
| Initial service | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| **Multifleet SCD 30** | | |

*Change every 50 hours*

| USE | | CLIMATE |
|---|---|---|
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| **Agrisynth LSP Ultra FE 5W-30** | **Agrisynth LSP 10W-40** | **Kroontrak CVT 10W-40** |

*Change every 50 hours*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

# WACKER NEUSON TRACKED EXCAVATORS 3703 YANMAR 4TNE88-ENSR (AD00001->)

| USE | | CLIMATE |
|---|---|---|
| Initial service | | Cold |
| **PRODUCT RECOMMENDATION 1** | | |
| **Multifleet SCD 10W** | | |
| *Change every 50 hours* | | |

## HYDRAULIC SYSTEM
Capacity: 45 liter (Hydraulic system including tank), Capacity: 27 liter (Hydraulic tank)

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | |
| **Perlus Biosynth 46** | **Perlus H 46** | |
| *Change every 1000 hours/ 12 months* | | |

| USE | | CLIMATE |
|---|---|---|
| Biodegradable oil | | Moderate |
| **PRODUCT RECOMMENDATION 1** | | |
| **Perlus Biosynth 46** | | |
| *Change every 1000 hours/ 12 months* | | |

## GREASE POINTS/NIPPLES

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| **PRODUCT RECOMMENDATION 1** | | |
| **MoS2 Grease EP 2** | | |
| *Change every 10 hours* | | |

## COOLING SYSTEM
Capacity: 6 liter (Engine only)

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | **PRODUCT RECOMMENDATION 3** |
| **Coolant SP 15+** | **Coolant SP 12** | **Coolant -38 Organic NF** |
| *Change every 1000 hours/ 12 months* | | |

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

# WACKER NEUSON TRACKED EXCAVATORS 3703 YANMAR 4TNE88-ENSR (AD00001->)

## SWING RING GEARING

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|---|---|---|
| **Q5 MP Calcep Grease EP 2** | **MP Lithep Grease EP 2** | |

## TRAVEL REDUCTION UNIT
Capacity: 1,3 liter (each)

| USE | CLIMATE |
|---|---|
| Normal, <- 10/2006 | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|---|---|---|
| **Gearlube GL-5 80W-90** | **Unigear HS GL-3/GL-5 80W-90** | |

*Check every 50 hours, change every 1000 hours/ 12 months*

| USE | CLIMATE |
|---|---|
| Normal, 10/2006 -> | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|---|---|---|
| **Gearlube GL-5 80W-90** | **Unigear HS GL-3/GL-5 80W-90** | |

*Check every 50 hours, change every 1000 hours/ 12 months*

| USE | CLIMATE |
|---|---|
| Initial service, <- 10/2006 | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|---|---|---|
| **Gearlube GL-5 80W-90** | **Unigear HS GL-3/GL-5 80W-90** | |

*Change every 50 hours*

| USE | CLIMATE |
|---|---|
| Initial service, 10/2006 -> | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|---|---|---|
| **Gearlube GL-5 80W-90** | **Unigear HS GL-3/GL-5 80W-90** | |

*Change every 50 hours*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367