

# WERKLUST WHEELED LOADERS WG WG 45D CUMMINS 6BT 8.3C

**ENGINE** Cummins 6BT8.3C

Capacity: 23,8 liter, Filter capacity: 0,9 liter

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Agridiesel CRD+ 15W-40**

## PRODUCT RECOMMENDATION 2

**Dieselfleet CD+ 15W-40**

## PRODUCT RECOMMENDATION 3

**Multifleet SHPD 15W-40***Change every 500 hours***DIFFERENTIAL FRONT** ZF AP 411 DK

Capacity: 21 liter

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Gearlube Racing 75W-140**

## PRODUCT RECOMMENDATION 2

**Gearlube LS 80W-90**

## PRODUCT RECOMMENDATION 3

**Unigear LS GL-3/GL-5 85W-140***Check every 100 hours, change every 600 hours***DIFFERENTIAL REAR** ZF AP 409 DK

Capacity: 15 liter

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Gearlube Racing 75W-140**

## PRODUCT RECOMMENDATION 2

**Gearlube LS 80W-90**

## PRODUCT RECOMMENDATION 3

**Unigear LS GL-3/GL-5 85W-140***Check every 100 hours, change every 600 hours***HUB REDUCTIONS FRONT**

Capacity: 5 liter

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Gearlube Racing 75W-140**

## PRODUCT RECOMMENDATION 2

**Gearlube LS 80W-90**

## PRODUCT RECOMMENDATION 3

**Unigear LS GL-3/GL-5 85W-140***Check every 100 hours, change every 600 hours***HUB REDUCTIONS REAR**

Capacity: 5,5 liter

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Gearlube Racing 75W-140**

## PRODUCT RECOMMENDATION 2

**Gearlube LS 80W-90**

## PRODUCT RECOMMENDATION 3

**Unigear LS GL-3/GL-5 85W-140***Check every 100 hours, change every 600 hours*

# WERKLUST WHEELED LOADERS WG WG 45D CUMMINS 6BT 8.3C

**TRANSMISSION POWERSHIFT ZF 4WG200 4/3**

Capacity: 28 liter (Dry fill), Capacity: 16 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Kroontrak CVT 10W-40</b>	<b>Kroontrak MTH 10W-30</b>	<b>Synfleet SHPD 10W-40</b>

*Change every 600 hours*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>ATF Almirol</b>	<b>ATF Dexron II-D</b>

*Change every 600 hours***HYDRAULIC SYSTEM**

Capacity: 175 liter (Hydraulic tank)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Perlus H 46</b>	<b>Perlus AF 46</b>

*Change every 2400 hours*

USE	CLIMATE
Biodegradable oil	Moderate

PRODUCT RECOMMENDATION 1	
<b>Perlus Biosynth 46</b>	

**HYDRAULIC BRAKE SYSTEM**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
<b>Multifleet SCD 10W</b>	

*Change every 2400 hours***GREASE POINTS/NIPPLES**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

# WERKLUST WHEELED LOADERS WG WG 45D CUMMINS 6BT 8.3C

**COOLING SYSTEM**

Capacity: 29,9 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Coolant SP 15+</b>	<b>Coolant SP 12</b>	<b>Coolant -38 Organic NF</b>

*Change every 2400 hours*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*