## WILLE ARTICULATED LOADERS 455B DETROIT D754 TE3



ENGINE D754 TE3 Capacity: 7-10 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Synfleet SHPD 10W-40	Multifleet SHPD 10W-40
Check every 10 hours, change every 300	hours/ 12 months	
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Synfleet SHPD 10W-40	Multifleet SHPD 10W-40
Check every 10 hours, change every 150	hours/ 12 months	
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Synfleet SHPD 10W-40	Multifleet SHPD 10W-40
Charles avery 10 hours shares avery 50 h	:	

Check every 10 hours, change every 50 hours

DIFFERENTIAL FRONT Capacity: 7,1 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	

DIFFERENTIAL REAR Capacity: 7,1 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	

HUB REDUCTIONS FRONT Capacity: 0,35 liter (each hub)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	

## WILLE ARTICULATED LOADERS 455B DETROIT D754 TE3



HUB REDUCTIONS REAR Capacity: 0,35 liter (each hub)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	

## TRANSMISSION HYDROSTATIC

Capacity: 0,9 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

Capacity: 60 liter		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 68	Perlus AF 68	

COOLING SYSTEM Capacity: 5 liter (Engine only), Capacity: 15 liter (Total system volume)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.