

# WIRTGEN COLD MILLING MACHINES

## 1300DC 05.20.0001-> 05.20.0058



**ENGINE** Mercedes-Benz OM442LA  
Capacity: 23 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Agridiesel CRD+ 15W-40</b>	<b>Dieselfleet CD+ 15W-40</b>

*Check every 10 hours, change every 250 hours/ 12 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Synfleet SHPD 10W-40</b>	<b>Armado Synth 5W-30</b>

*Check every 10 hours, change every 250 hours/ 12 months*

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Agridiesel CRD+ 15W-40</b>	<b>Dieselfleet CD+ 15W-40</b>

*Change every 50 hours*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Synfleet SHPD 10W-40</b>	<b>Armado Synth 5W-30</b>

*Change every 50 hours*

**HYDRAULIC SYSTEM**  
Capacity: 280 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
<b>Perlus H 68</b>	

*Check every 10 hours, change every 1000 hours/ 12 months*

### GREASE POINTS/NIPPLES GENERAL

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
<b>MoS2 Grease EP 2</b>	

*Check every 10 hours*

# WIRTGEN COLD MILLING MACHINES

## 1300DC 05.20.0001-> 05.20.0058



### GREASE POINTS/NIPPLES SPECIAL

We are unable to give a standard recommendation for this component. Please contact our service department.

### COOLING SYSTEM ENGINE

Capacity: 80 liter

#### USE

Normal

#### CLIMATE

Moderate

#### PRODUCT RECOMMENDATION 1

**Coolant SP 11**

*Check every 10 hours, change every 12 months*

### DRUM SHELL

Capacity: 140 liter

#### USE

Normal

#### CLIMATE

Moderate

#### PRODUCT RECOMMENDATION 1

**Coolant -38 Organic NF**

#### PRODUCT RECOMMENDATION 2

**Coolant -26**

### MILLING DRUM GEARBOX

Capacity: 19,7 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

### PUMP SPLITTER GEARBOX

Capacity: 4,2 liter

#### USE

Normal

#### CLIMATE

Moderate

#### PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90**

#### PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90**

*Check every 10 hours, change every 500 hours/ 12 months*

#### USE

Initial service

#### CLIMATE

Moderate

#### PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90**

#### PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90**

*Change every 50 hours*

# WIRTGEN COLD MILLING MACHINES

## 1300DC 05.20.0001-> 05.20.0058

**TRAVEL REDUCTION UNIT**

Capacity: 1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	

*Check every 50 hours, change every 500 hours/ 12 months*

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	

*Change every 50 hours***WATER TANK FILLER PUMP**

Capacity: 0,25 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	

*Change every 12 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.