WIRTGEN COLD MILLING MACHINES 1500DC 05.20.0001-> 05.20.0058



| ENGINE Mercedes-Benz OM442LA Capacity: 23 liter | | |
|--|--------------------------|---------------|
| USE | | CLIMATE |
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Agridiesel CRD+ 15W-40 | Dieselfleet CD+ 15W-40 | |
| Check every 10 hours, change every | 250 hours/ 12 months | · |
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Synfleet SHPD 10W-40 | Armado Synth 5W-30 | |
| Check every 10 hours, change every | 250 hours/ 12 months | |
| USE | | CLIMATE |
| Initial service | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Agridiesel CRD+ 15W-40 | Dieselfleet CD+ 15W-40 | |
| Change every 50 hours | | |
| USE | | CLIMATE |
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Synfleet SHPD 10W-40 | Armado Synth 5W-30 | |
| Change every 50 hours | | |
| | | |
| HYDRAULIC SYSTEM | | |
| Capacity: 280 liter | | |
| USE | | CLIMATE |

| HYDRAULIC SYSTEM Capacity: 280 liter | | |
|--------------------------------------|-----|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Perlus H 68 | | |
| 01 | 3 1 | |

Check every 10 hours, change every 1000 hours/ 12 months

| GREASE POINTS/NIPPLES GENERAL | | |
|-------------------------------|--|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| MoS2 Grease EP 2 | | |
| Check every 10 hours | | |

WIRTGEN COLD MILLING MACHINES 1500DC 05.20.0001-> 05.20.0058



GREASE POINTS/NIPPLES SPECIAL

We are unable to give a standard recommendation for this component. Please contact our service department.

| COOLING SYSTEM ENGINE Capacity: 80 liter | |
|--|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Coolant SP 11 | |
| Check every 10 hours, change every 1 | onths |

| DRUM SHELL Capacity: 170 liter | |
|-----------------------------------|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Coolant SP 11 | |

MILLING DRUM GEARBOX

Capacity: 17,4 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

| PUMP SPLITTER GEARBOX Capacity: 4,2 liter | | |
|---|-----------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |
| Check every 10 hours, change every 500 hours/ 12 months | | |

| USE | | CLIMATE |
|--------------------------|-----------------------------|----------|
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |
| Change every 50 hours | | |

WIRTGEN COLD MILLING MACHINES 1500DC 05.20.0001-> 05.20.0058



| TRAVEL REDUCTION UNIT Capacity: 1 liter | | |
|---|-----------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |
| Check every 50 hours, change every 500 | hours/ 12 months | |
| USE | | CLIMATE |
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |
| Change every 50 hours | | |

| WATER TANK FILLER PUMP Capacity: 0,25 liter | | |
|--|-----------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |
| Change every 12 months | , | • |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.