

WIRTGEN COLD MILLING MACHINES

2000DC 05.20.0100 ->



ENGINE Mercedes-Benz OM442LA
Capacity: 23 liter

USE Normal		CLIMATE Moderate
----------------------	--	----------------------------

PRODUCT RECOMMENDATION 1 Agrisynth LSP Ultra 10W-40	PRODUCT RECOMMENDATION 2 Agrisynth LSP 10W-40	PRODUCT RECOMMENDATION 3 Agridiesel CRD+ 15W-40
--	--	--

Check every 10 hours, change every 250 hours/ 12 months

USE Initial service		CLIMATE Moderate
-------------------------------	--	----------------------------

PRODUCT RECOMMENDATION 1 Agrisynth LSP Ultra 10W-40	PRODUCT RECOMMENDATION 2 Agrisynth LSP 10W-40	PRODUCT RECOMMENDATION 3 Agridiesel CRD+ 15W-40
--	--	--

Change every 50 hours

HYDRAULIC SYSTEM
Capacity: 280 liter

USE Normal		CLIMATE Moderate
----------------------	--	----------------------------

PRODUCT RECOMMENDATION 1 Perlus H 68		
---	--	--

Check every 10 hours, change every 1000 hours/ 12 months

GREASE POINTS/NIPPLES GENERAL

USE Normal		CLIMATE Moderate
----------------------	--	----------------------------

PRODUCT RECOMMENDATION 1 MoS2 Grease EP 2		
--	--	--

Check every 10 hours

GREASE POINTS/NIPPLES SPECIAL

We are unable to give a standard recommendation for this component. Please contact our service department.

COOLING SYSTEM CHARGE COOLING
Capacity: 22,5 liter

USE Normal		CLIMATE Moderate
----------------------	--	----------------------------

PRODUCT RECOMMENDATION 1 Coolant -38 Organic NF	PRODUCT RECOMMENDATION 2 Coolant -26	
--	---	--

Check every 10 hours, change every 12 months

WIRTGEN COLD MILLING MACHINES

2000DC 05.20.0100 ->



COOLING SYSTEM ENGINE

Capacity: 72 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Check every 10 hours, change every 12 months

DRUM SHELL

Capacity: 265 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

MILLING DRUM GEARBOX

Capacity: 15 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Abacot MEP Synth 220		

Check every 50 hours, change every 500 hours/ 12 months

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Abacot MEP Synth 220		

Change every 50 hours

WIRTGEN COLD MILLING MACHINES

2000DC 05.20.0100 ->



PUMP SPLITTER GEARBOX

Capacity: 4,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 10 hours, change every 500 hours/ 12 months

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 50 hours

TRAVEL REDUCTION UNIT

Capacity: 1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 50 hours, change every 500 hours/ 12 months

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 50 hours

WATER TANK FILLER PUMP

Capacity: 0,25 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.