

**WIRTGEN COLD MILLING MACHINES W350****02.03.0595 -> (2005 AND AFTER)**

**ENGINE** KHD F4L-2011  
Capacity: 10,5 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2      | PRODUCT RECOMMENDATION 3    |
|-----------------------------|-------------------------------|-----------------------------|
| <b>Kroontrak CVT 10W-40</b> | <b>Agridiesel CRD+ 15W-40</b> | <b>Kroontrak MTH 10W-30</b> |

*Check every 10 hours, change every 250 hours/ 12 months*

| USE             | CLIMATE  |
|-----------------|----------|
| Initial service | Moderate |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2      | PRODUCT RECOMMENDATION 3    |
|-----------------------------|-------------------------------|-----------------------------|
| <b>Kroontrak CVT 10W-40</b> | <b>Agridiesel CRD+ 15W-40</b> | <b>Kroontrak MTH 10W-30</b> |

*Change every 50 hours*

**HYDRAULIC SYSTEM**  
Capacity: 60 liter

| USE    | CLIMATE       |
|--------|---------------|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1 |  |  |
|--------------------------|--|--|
| <b>Perlus H 68</b>       |  |  |

*Check every 10 hours, change every 1000 hours/ 12 months*

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1  | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3  |
|---------------------------|--------------------------|---------------------------|
| <b>Perlus Biosynth 46</b> | <b>Perlus H 46</b>       | <b>Perlus Biosynth 32</b> |

*Check every 10 hours, change every 1000 hours/ 12 months*

**GREASE POINTS/NIPPLES**

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 |  |  |
|--------------------------|--|--|
| <b>MoS2 Grease EP 2</b>  |  |  |

*Check every 10 hours*

**WIRTGEN COLD MILLING MACHINES W350****02.03.0595 -> (2005 AND AFTER)****MILLING DRUM GEARBOX**

Capacity: 5,5 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Abacot MEP Synth 220***Check every 50 hours, change every 500 hours/ 12 months*

| USE             | CLIMATE  |
|-----------------|----------|
| Initial service | Moderate |

PRODUCT RECOMMENDATION 1

**Abacot MEP Synth 220***Change every 50 hours***TRAVEL REDUCTION UNIT**

Capacity: 1,5 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90**

PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90***Check every 50 hours, change every 500 hours/ 12 months*

| USE             | CLIMATE  |
|-----------------|----------|
| Initial service | Moderate |

PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90**

PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90***Change every 50 hours*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.