XCMG WHEELED LOADERS ZL50G



| ENGINE WD 615G.220 | | |
|---------------------------|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Dieselfleet CD+ 15W-40 | Multifleet SHPD 15W-40 | Multifleet SCD 40 |
| USE | | CLIMATE |
| Normal | | Cold |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Kroontrak MTH 10W-30 | Synfleet SHPD 10W-40 | Multifleet SHPD 10W-40 |

| Normal Moderate PRODUCT RECOMMENDATION 1 Coorlybe J. S. 20W, 00 | DIFFERENTIAL FRONT Capacity: 36 liter | |
|---|--|----------|
| PRODUCT RECOMMENDATION 1 | | |
| | Normal | Moderate |
| Coorlybo L S 90W 00 | PRODUCT RECOMMENDATION 1 | |
| Gearlube LS 60W-90 | Gearlube LS 80W-90 | |

| DIFFERENTIAL REAR Capacity: 36 liter | |
|--------------------------------------|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Gearlube LS 80W-90 | |

| TRANSMISSION POWERSHIFT Capacity: 45 liter | |
|---|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Multifleet SCD 10W | |

XCMG WHEELED LOADERS ZL50G



| HYDRAULIC SYSTEM Capacity: 200 liter | |
|--------------------------------------|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Perlus H 46 | |
| USE | CLIMATE |
| Normal | Cold |
| PRODUCT RECOMMENDATION 1 | |
| Perlus H 32 | |
| use Normal PRODUCT RECOMMENDATION 1 | |

GREASE POINTS/NIPPLES

We are unable to give a standard recommendation for this component. Please contact our service department.

| COOLING SYSTEM | | | |
|--------------------------|--------------------------|----------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| Coolant -38 Organic NF | Coolant -26 | | |

| BRAKE ACTUATION SYSTEM | |
|--------------------------|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Drauliquid DOT 3 | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.