

# YALE FORKLIFT TRUCKS, DIESEL GDP 20 AF MAZDA HA

**ENGINE** Mazda HA

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

**HDX 30***Change every 1 months/ 200 hours*

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1

**HDX 30***Change every 50 hours/ 1 week***DIFFERENTIAL**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90**

PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90**

PRODUCT RECOMMENDATION 3

**Gearlube GL-5 85W-140****TRANSMISSION AUTOMATIC**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**ATF Dexron II-D****HYDRAULIC SYSTEM**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**HDX 10W***Change every 6 months/ 1200 hours***HYDRAULIC BRAKE SYSTEM**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Drauliquid DOT 3***Change every 6 months/ 1200 hours*

# YALE FORKLIFT TRUCKS, DIESEL GDP 20 AF MAZDA HA



## GREASE POINTS/NIPPLES

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

**MoS2 Grease EP 2**

## GREASE POINTS/NIPPLES BEARINGS

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

**MoS2 Grease EP 2**

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.