

YALE FORKLIFT TRUCKS, DIESEL GDP 20 PD



ENGINE

USE

Normal

CLIMATE

Tropical

PRODUCT RECOMMENDATION 1

HDX 30*Change every 1 months/ 200 hours*

USE

Normal

CLIMATE

Mediterranean

PRODUCT RECOMMENDATION 1

HDX 20W-20*Change every 1 months/ 200 hours*

USE

Normal

CLIMATE

Arctic

PRODUCT RECOMMENDATION 1

HDX 10W*Change every 1 months/ 200 hours*

USE

Initial service

CLIMATE

Tropical

PRODUCT RECOMMENDATION 1

HDX 30*Change every 50 hours/ 1 week*

USE

Initial service

CLIMATE

Mediterranean

PRODUCT RECOMMENDATION 1

HDX 20W-20*Change every 50 hours/ 1 week*

USE

Initial service

CLIMATE

Arctic

PRODUCT RECOMMENDATION 1

HDX 10W*Change every 50 hours/ 1 week*

DIFFERENTIAL

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 85W-140

PRODUCT RECOMMENDATION 2

Unigear LS GL-3/GL-5 85W-140

YALE FORKLIFT TRUCKS, DIESEL GDP 20 PD



TRANSMISSION AUTOMATIC Yale

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

HYDRAULIC SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 32		

Change every 6 months/ 1200 hours

HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

Change every 6 months/ 1200 hours

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

GREASE POINTS/NIPPLES BEARINGS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.