YALE FORKLIFT TRUCKS, DIESEL GDP 40 LJ (2000-2006)



| se Normal RODUCT RECOMMENDATION 1 | | climate Mediterranean |
|---|--------------------------|--------------------------|
| | | Mediterranean |
| RODUCT RECOMMENDATION 1 | 1 | moditoriaricari |
| | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agridiesel CRD+ 15W-40 | Dieselfleet CD+ 15W-40 | Multifleet SHPD 15W-40 |
| Change every 1 months/ 200 hours | | |
| SE | | CLIMATE |
| lormal | | Moderate |
| RODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| (roontrak MTH 10W-30 | Synfleet SHPD 10W-40 | Armado Synth 5W-30 |
| Change every 1 months/ 200 hours | | |
| SE | | CLIMATE |
| nitial service | | Mediterranean |
| RODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agridiesel CRD+ 15W-40 | Dieselfleet CD+ 15W-40 | Multifleet SHPD 15W-40 |
| Change every 50 hours/ 1 week | | |
| SE | | CLIMATE |
| nitial service | | Moderate |
| RODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| (roontrak MTH 10W-30 | Synfleet SHPD 10W-40 | Armado Synth 5W-30 |
| Change every 50 hours/ 1 week | | |

| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | Gearlube GL-5 85W-140 |
|--------------------------|-----------------------------|--------------------------|
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Normal | | Moderate |
| USE | | CLIMATE |

| TRANSMISSION AUTOMATIC | | |
|---------------------------|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agrifluid Synth XHP Ultra | Agrifluid HT-Plus | Kroontrak MTH 10W-30 |

YALE FORKLIFT TRUCKS, DIESEL GDP 40 LJ (2000-2006)



| HYDRAULIC SYSTEM | |
|-----------------------------------|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| HDX 10W | |
| Change every 6 months/ 1200 hours | |
| | |
| HYDRAULIC BRAKE SYSTEM | |
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Drauliquid DOT 3 | |
| Change every 6 months/ 1200 hours | |

| GREASE POINTS/NIPPLES | |
|--------------------------|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| MoS2 Grease EP 2 | |

| GREASE POINTS/NIPPLES BEARINGS | | |
|--------------------------------|--|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| MoS2 Grease EP 2 | | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.