

AHLMANN SWING LOADERS AS AS 11

DEUTZ BF4M1012E (1996-2000)



ENGINE Deutz BF4M-1012E
Capacity: 10 liter

USE	CLIMATE
Normal, fuel sulfur level <0,5 %	Mediterranean

PRODUCT RECOMMENDATION 1

Multifleet SHPD 20W-50

Check every 10 hours, change every 500 hours/ 12 months

USE	CLIMATE
Normal, fuel sulfur level <0,5 %	Moderate

PRODUCT RECOMMENDATION 1

Agrisynth LSP 10W-40

PRODUCT RECOMMENDATION 2

Kroontrak CVT 10W-40

PRODUCT RECOMMENDATION 3

Agrisynth MSP 10W-40

Check every 10 hours, change every 500 hours/ 12 months

DIFFERENTIAL FRONT
Capacity: 8,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90

Change every 1500 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90

Change every 500 hours

DIFFERENTIAL REAR
Capacity: 10 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90

Change every 1500 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90

Change every 500 hours

AHLMANN SWING LOADERS AS AS 11

DEUTZ BF4M1012E (1996-2000)



HUB REDUCTIONS FRONT

Capacity: 1,75 liter (each hub)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90*Change every 500 hours*

HUB REDUCTIONS REAR

Capacity: 1,75 liter (each hub)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90*Change every 500 hours*

POWERSHIFT GEAR

Capacity: 2,75 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Dieselfleet CD+ 15W-40

PRODUCT RECOMMENDATION 2

Multifleet SHPD 15W-40*Change every 1500 hours*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

Dieselfleet CD+ 15W-40

PRODUCT RECOMMENDATION 2

Multifleet SHPD 15W-40*Change every 500 hours*

HYDRAULIC SYSTEM

Capacity: 140 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Perlus H 46*Change every 1500 hours*

AHLMANN SWING LOADERS AS AS 11

DEUTZ BF4M1012E (1996-2000)



GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

COOLING SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 11		

Change every 2000 hours/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.