

AICHI TRACKED BOOMLIFTS RZ/SR/ISR

ISR40B ISUZU 3LD1 (2001 AND AFTER)



ENGINE Isuzu 3LD1
Capacity: 6,3 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|-------------------------------------|------------------------------|-------------------------------|
| Agrisynth LSP Ultra FE 5W-30 | Agridiesel MSP 15W-40 | Agridiesel CRD+ 15W-40 |

Change every 250 hours

| USE | CLIMATE |
|-----------------|----------|
| Initial service | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|-------------------------------------|------------------------------|-------------------------------|
| Agrisynth LSP Ultra FE 5W-30 | Agridiesel MSP 15W-40 | Agridiesel CRD+ 15W-40 |

Change every 50 hours

HYDRAULIC SYSTEM
Capacity: 145 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|--------------------------|--|--|
| Perlus H 22 | | |

Change every 1200 hours/ 12 months

| USE | CLIMATE |
|--------|---------|
| Normal | Arctic |

| PRODUCT RECOMMENDATION 1 | | |
|--------------------------|--|--|
| Perlus H 15 | | |

Change every 1200 hours/ 12 months

GREASE POINTS/NIPPLES GENERAL

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|--------------------------|---------------------------------|------------------------------|
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

Change every 100 hours

AICHI TRACKED BOOMLIFTS RZ/SR/ISR

ISR40B ISUZU 3LD1 (2001 AND AFTER)

**COOLING SYSTEM**

Capacity: 2,5 liter (Engine only)

| USE | | CLIMATE |
|-------------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Coolant -38 Organic NF | | |

SWING REDUCTION GEARBOX

Capacity: 1,7 liter

| USE | | CLIMATE |
|-----------------------------|------------------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-4 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |

Change every 1200 hours/ 12 months

| USE | | CLIMATE |
|-----------------------------|------------------------------------|----------|
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-4 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |

*Change every 3 months/ 300 hours***TRAVEL REDUCTION GEARBOX**

Capacity: 1 liter

| USE | | CLIMATE |
|-----------------------------|------------------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-4 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |

Change every 1200 hours/ 12 months

| USE | | CLIMATE |
|-----------------------------|------------------------------------|----------|
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-4 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |

Change every 3 months/ 300 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.