## AICHI TRACKED BOOMLIFTS RZ/SR/ISR SR210 ISUZU 4BD1-T (1997-2002)



| ENGINE 4BD1-T                |                          |                          |
|------------------------------|--------------------------|--------------------------|
| USE                          |                          | CLIMATE                  |
| Normal                       |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1     | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agrisynth LSP Ultra FE 5W-30 | Agridiesel MSP 15W-40    | Agridiesel CRD+ 15W-40   |
| Change every 250 hours       |                          | -<br>-                   |
| USE                          |                          | CLIMATE                  |
| Initial service              |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1     | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agrisynth LSP Ultra FE 5W-30 | Agridiesel MSP 15W-40    | Agridiesel CRD+ 15W-40   |

Change every 50 hours

| HYDRAULIC SYSTEM<br>Capacity: 250 liter (Hydraulic tank) |                          |          |  |
|--|--------------------------|----------|--|
| USE  |                          | CLIMATE  |  |
| Normal   |                          | Moderate |  |
| PRODUCT RECOMMENDATION 1                                 | PRODUCT RECOMMENDATION 2 |          |  |
| Perlus Biosynth 32                                       | Perlus H 32              |          |  |
|  |                          | 1        |  |

Change every 1200 hours/ 12 months

| USE                                |   | CLIMATE |
|------------------------------------|---|---------|
| Normal                             |   | Arctic  |
| PRODUCT RECOMMENDATION 1           |   |         |
| Perlus H 15                        |   |         |
| Change every 1200 hours/ 12 months | · |         |

| GREASE POINTS/NIPPLES GENERAL<br>USE CLIMATE |                          |  |
|--|--------------------------|--|
|  | CLIMATE                  |  |
|  | Moderate                 |  |
| PRODUCT RECOMMENDATION 2                     | PRODUCT RECOMMENDATION 3 |  |
| Q5 MP Calcep Grease EP 2                     | MP Lithep Grease EP 2    |  |
|  | PRODUCT RECOMMENDATION 2 |  |

Change every 100 hours

| COOLING SYSTEM           |          |
|--------------------------|----------|
| USE                      | CLIMATE  |
| Normal                   | Moderate |
| PRODUCT RECOMMENDATION 1 |          |
| Coolant -38 Organic NF   |          |

## AICHI TRACKED BOOMLIFTS RZ/SR/ISR SR210 ISUZU 4BD1-T (1997-2002)



| SWING REDUCTION GEARBOX<br>Capacity: 1,1 liter |  |          |
|--|--|----------|
| USE  |  | CLIMATE  |
| Normal   |  | Moderate |
| PRODUCT RECOMMENDATION 1                       |  |          |
| Abacot MEP 460                                 |  |          |
| Change every 1200 hours/ 12 months             |  |          |
| USE  |  | CLIMATE  |
| Initial service                                |  | Moderate |
| PRODUCT RECOMMENDATION 1                       |  |          |
| Abacot MEP 460                                 |  |          |
| Change every 3 months/ 300 hours               |  |          |
|  |  |          |

| TRAVEL REDUCTION GEARBOX<br>Capacity: 3,5 liter |  |          |
|---|--|----------|
| USE   |  | CLIMATE  |
| Normal  |  | Moderate |
| PRODUCT RECOMMENDATION 1                        |  |          |
| Multifleet SCD 30                               |  |          |
| Change every 1200 hours/ 12 months              |  |          |
| USE   |  | CLIMATE  |
| Initial convice                                 |  | Madarata |

| Initial service                  |  | Moderate |
|----------------------------------|--|----------|
| PRODUCT RECOMMENDATION 1         |  |          |
| Multifleet SCD 30                |  |          |
| Change every 3 months/ 300 hours |  |          |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.