## AMKODOR FORKLIFTERS 451A (74 KW) MMZ D-245



| ENGINE MMZ D-245<br>Capacity: 15 liter |                          |                          |
|--|--------------------------|--------------------------|
| USE                                    |                          | CLIMATE                  |
| Normal, fuel sulfur level < 0,035 %    |                          | Mediterranean            |
| PRODUCT RECOMMENDATION 1               | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agrisynth LSP 10W-40                   | Kroontrak CVT 10W-40     | Agrisynth MSP 10W-40     |
| Change every 250 hours/ 12 months      |                          |                          |
| USE                                    |                          | CLIMATE                  |
| Normal, fuel sulfur level < 0,035 %    |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1               | PRODUCT RECOMMENDATION 2 |                          |
| Asyntho 5W-30                          | Armado Synth 5W-30       |                          |
| Change every 250 hours/ 12 months      |                          |                          |
| USE                                    |                          | CLIMATE                  |
| Normal, fuel sulfur level < 0,035 %    |                          | Arctic                   |
| PRODUCT RECOMMENDATION 1               |                          |                          |
| Multifleet SCD 20W-20                  |                          |                          |
| Change every 250 hours/ 12 months      |                          | ·                        |

| Change overly 200 mounts in the many services and the many services are the many services and the many services and the many services are the many service |                             |          |
|--|-----------------------------|----------|
|  |                             |          |
| AXLE FRONT Capacity: 15 liter  |                             |          |
| USE  |                             | CLIMATE  |
|  |                             |          |
| Normal   |                             | Moderate |
| PRODUCT RECOMMENDATION 1   | PRODUCT RECOMMENDATION 2    |          |
| Gearlube GL-5 80W-90   | Unigear HS GL-3/GL-5 80W-90 |          |
| Check every 250 hours, change ever   | ry 1000 hours               |          |
| USE  |                             | CLIMATE  |
| Initial service  |                             | Moderate |
| PRODUCT RECOMMENDATION 1   | PRODUCT RECOMMENDATION 2    |          |
| Gearlube GL-5 80W-90   | Unigear HS GL-3/GL-5 80W-90 |          |

Change every 125 hours

## AMKODOR FORKLIFTERS 451A (74 KW) MMZ D-245



| TRANSMISSION HYDROMECHANICAL GMF U35615 4/2 Capacity: 30 liter |          |          |
|--|----------|----------|
| USE  |          | CLIMATE  |
| Normal   |          | Moderate |
| PRODUCT RECOMMENDATION 1                                       |          |          |
| SP Matic 2032  |          |          |
| Check every 250 hours, change every 100                        | 00 hours |          |
| USE  |          | CLIMATE  |
| Initial service  |          | Moderate |
| PRODUCT RECOMMENDATION 1                                       |          |          |
| SP Matic 2032  |          |          |
| Change every 125 hours   |          |          |
| USE  |          | CLIMATE  |
| Second change only   |          | Moderate |
| PRODUCT RECOMMENDATION 1                                       |          |          |
| SP Matic 2032  |          |          |
| Change every 500 hours   |          |          |

| HYDRAULIC SYSTEM Capacity: 100 liter (Hydraulic tank) |               |
|---|---------------|
| USE   | CLIMATE       |
| Normal  | Mediterranean |
| PRODUCT RECOMMENDATION 1                              |               |
| Perlus H 46   |               |
| Change every 2000 hours                               |               |
| USE   | CLIMATE       |
| Normal  | Cold          |
| PRODUCT RECOMMENDATION 1                              |               |
| Perlus H 15   |               |
| Change every 2000 hours                               |               |

| USE                      |                          | CLIMATE                  |
|--------------------------|--------------------------|--------------------------|
| Normal                   |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease            | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2    |

## AMKODOR FORKLIFTERS 451A (74 KW) MMZ D-245



| GREASE POINTS/NIPPLES DRIVE SHAFT SPLINE CONNECTION |                          |                          |
|---|--------------------------|--------------------------|
| USE CLIMATE   |                          | CLIMATE                  |
| Normal  |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1                            | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease                                       | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2    |

| GREASE POINTS/NIPPLES GENERAL          |                          |                          |
|--|--------------------------|--------------------------|
| USE                                    |                          | CLIMATE                  |
| Normal                                 |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1               | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease Q5 MP Calcep Grease EP 2 |                          | MP Lithep Grease EP 2    |

| COOLING SYSTEM Capacity: 20 liter |          |
|-----------------------------------|----------|
| USE                               | CLIMATE  |
| Normal                            | Moderate |
| PRODUCT RECOMMENDATION 1          |          |
| Coolant -38 Organic NF            |          |
| Change every 24 months            |          |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.