

# AMMANN HEAVY LINE PLATES AVH AVH

## 5020 HATZ 1D50 S (2003 AND AFTER)

**ENGINE** Hatz 1D50

Capacity: 1,5 liter, Filter capacity: 0,1 liter

USE	CLIMATE
Normal	Mediterranean

## PRODUCT RECOMMENDATION 1

**Multifleet SHPD 20W-50***Change every 250 hours/ 12 months*

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Kroontrak CVT 10W-40**

## PRODUCT RECOMMENDATION 2

**Kroontrak MTH 10W-30**

## PRODUCT RECOMMENDATION 3

**Synfleet SHPD 10W-40***Change every 250 hours/ 12 months***HYDRAULIC SYSTEM**

Capacity: 19 liter

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Perlus H 32***Change every 1000 hours/ 12 months*

USE	CLIMATE
Initial service	Moderate

## PRODUCT RECOMMENDATION 1

**Perlus H 32***Change every 500 hours***VIBRATOR UNIT**

Capacity: 1 liter

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Agrifluid Synth XHP Ultra**

## PRODUCT RECOMMENDATION 2

**Kroontrak MTH 10W-30***Change every 250 hours/ 12 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.