

ATLET COUNTERBALANCE FORKLIFT TRUCKS, ELECTRIC EF/EH/ET EF-20 (2005 AND AFTER)



DIFFERENTIAL FRONT

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrifluid HT-Plus	Agrifluid HT	
<i>Change every 12 months/ 2400 hours</i>		

REDUCTION GEARS

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		
<i>Change every 12 months/ 2400 hours</i>		

USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	SP Gear 5015	Gearlube GL-4 80W
<i>Change every 12 months/ 2400 hours</i>		

HYDRAULIC SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 32		
<i>Change every 6 months/ 1200 hours</i>		

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Perlus H 15		
<i>Change every 6 months/ 1200 hours</i>		

HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	
<i>Change every 12 months/ 2400 hours</i>		

ATLET COUNTERBALANCE FORKLIFT TRUCKS, ELECTRIC EF/EH/ET EF-20 (2005 AND AFTER)



GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Grease EP 1		
<i>Change every 3 months/ 600 hours</i>		

GREASE POINTS/NIPPLES WHEEL BEARINGS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
<i>Change every 12 months/ 2400 hours</i>		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.