PRODUCT RECOMMENDATION

AUSA WHEELED DUMPERS 250 RMA
ISUZU 3LB1 (1996-2005)

ENGINE Isuzu 3LB1
Capacity: 5,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Dieselfleet CD+ 15W-40	**Multifleet SHPD 15W-40**	**Multifleet SCD 30**

Change every 250 hours/ 6 months

USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Multifleet SCD 20W-20		

Change every 250 hours/ 6 months

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Dieselfleet CD+ 15W-40	**Multifleet SHPD 15W-40**	**Multifleet SCD 30**

Change every 50 hours

USE		CLIMATE
Initial service		Cold
PRODUCT RECOMMENDATION 1		
Multifleet SCD 20W-20		

Change every 50 hours

TRANSMISSION DIFFERENTIAL
Capacity: 2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

Change every 1000 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

Change every 50 hours

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

AUSA WHEELED DUMPERS 250 RMA ISUZU 3LB1 (1996-2005)

HYDRAULIC SYSTEM
Capacity: 30 liter (Hydraulic tank)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 68		

Change every 1000 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 68		

Change every 100 hours

HYDRAULIC ACTUATION OIL IMMERSED BRAKES
Capacity: 0,25 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
LHM +		

Change every 500 hours

ARTICULATION JOINTS
We are unable to give a standard recommendation for this component. Please contact our service department.

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	**Q5 MP Calcep Grease EP 2**	**MP Lithep Grease EP 2**

Change every 50 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367