

AUSA REACH TRUCKS TAURULIFT T144H

(2010 AND AFTER)



ENGINE Kubota
Capacity: 5,1 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Multifleet SHPD 20W-50

Check every 10 hours, change every 150 hours/ 12 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Synfleet SHPD 10W-40

PRODUCT RECOMMENDATION 2

Dieselfleet CD+ 15W-40

PRODUCT RECOMMENDATION 3

Multifleet SHPD 10W-40

Check every 10 hours, change every 150 hours/ 12 months

DIFFERENTIAL FRONT
Capacity: 1,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90

Check every 1 months, change every 12 months/ 750 hours

HYDRAULIC SYSTEM
Capacity: 32 liter (Hydraulic tank)

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1

Perlus H 68

Check every 10 hours, change every 900 hours

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Perlus Biosynth 46

PRODUCT RECOMMENDATION 2

Perlus H 46

Check every 10 hours, change every 900 hours

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1

Perlus Biosynth 32

PRODUCT RECOMMENDATION 2

Perlus H 32

Check every 10 hours, change every 900 hours

AUSA REACH TRUCKS TAURULIFT T144H

(2010 AND AFTER)



HYDRAULIC SYSTEM BRAKING & INCHING

Capacity: 1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Agrifluid Synth XHP Ultra	Kroontrak MTH 10W-30

Check every 40 hours, change every 900 hours

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.