

AVELING BARFORD WHEELED LOADERS **WL-26**


ENGINE Cummins 6CT8.3

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	

DIFFERENTIAL FRONT

USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1		
Gearlube GL-5 85W-140		

Change every 800 hours/ 12 months

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 800 hours/ 12 months

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	SP Gear 1071	

Change every 800 hours/ 12 months

AVELING BARFORD WHEELED LOADERS **WL-26**



DIFFERENTIAL REAR

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1

Gearlube GL-5 85W-140*Change every 800 hours/ 12 months*

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90*Change every 800 hours/ 12 months*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

SP Gear 5015

PRODUCT RECOMMENDATION 2

SP Gear 1071*Change every 800 hours/ 12 months*

HUB REDUCTIONS FRONT

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1

Gearlube GL-5 85W-140*Change every 800 hours/ 12 months*

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90*Change every 800 hours/ 12 months*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

SP Gear 5015

PRODUCT RECOMMENDATION 2

SP Gear 1071*Change every 800 hours/ 12 months*

AVELING BARFORD WHEELED LOADERS **WL-26**


PLANETARY GEARS REAR

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1

Gearlube GL-5 85W-140*Change every 800 hours/ 12 months*

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90*Change every 800 hours/ 12 months*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

SP Gear 5015

PRODUCT RECOMMENDATION 2

SP Gear 1071*Change every 800 hours/ 12 months*
TRANSMISSION Kawasaki

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Multifleet SCD 10W

PRODUCT RECOMMENDATION 2

ATF Dexron II-D
TRANSMISSION Shensu

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Multifleet SCD 10W

PRODUCT RECOMMENDATION 2

ATF Dexron II-D

AVELING BARFORD WHEELED LOADERS **WL-26**



HYDRAULIC SYSTEM

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1		
Perlus H 68		

Change every 1200 hours/ 12 months

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1		
Perlus H 46		

Change every 1200 hours/ 12 months

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1		
Perlus H 32		

Change every 1200 hours/ 12 months

HYDRAULIC BRAKE SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Drauliquid-S DOT 4		

GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.