

Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	Multifleet SCD 30
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	Multifleet SCD 30
Change every 250 hours/ 6 months		
use Normal, fuel sulfur level <0,5 %		climate Moderate
PRODUCT RECOMMENDATION 1  Kroontrak MTH 10W-30	PRODUCT RECOMMENDATION 2 Synfleet SHPD 10W-40	PRODUCT RECOMMENDATION 3  Multifleet SHPD 10W-40
Change every 250 hours/ 6 months	'	
use Normal, fuel sulfur level <0,5 %		CLIMATE Cold
PRODUCT RECOMMENDATION 1		
Multifleet SCD 20W-20		
Change every 250 hours/ 6 months		
use Normal, fuel sulfur level <0,5 %		climate Arctic
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		
Change every 250 hours/ 6 months		
use Initial service		climate Tropical
PRODUCT RECOMMENDATION 1		Πορισαί
Multifleet SCD 40		
Change every 100 hours		
Change every 100 hours		CLIMATE
Change every 100 hours	PRODUCT RECOMMENDATION 2	CLIMATE  Mediterranean  PRODUCT RECOMMENDATION 3



use Initial service		climate Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Multifleet SHPD 10W-40
Change every 100 hours		
USE		CLIMATE
Initial service		Cold
PRODUCT RECOMMENDATION 1		
Multifleet SCD 20W-20		
Change every 100 hours		
USE		CLIMATE
Initial service		Arctic
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		
Change every 100 hours	•	

<b>DIFFERENTIAL FRONT</b> Bell Capacity: 45 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Check every 250 hours, change eve	ery 500 hours	
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 100 hours

Change every 100 hours

## BELL EQUIPMENT ARTICULATED DUMP TRUCKS B-C-D-E SERIES B25 (6X4) DEUTZ BF6L513R



DIFFERENTIAL MIDDLE Bell Capacity: 45 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90		
Check every 250 hours, change every 500	hours		
USE		CLIMATE	
Initial service		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90		

FINAL DRIVES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Check every 250 hours, change ever	ry 500 hours	'
USE		CLIMATE

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Change every 100 hours	·	

TRANSMISSION ZF 6WG200 6/3 Capacity: 28 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	

	_				_
Check everv 250	) hours	change	every	1000	hours

Dollegoorweg 15

7602 EC Almelo

USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Kroontrak MTH 10W-30 Synfleet SHPD 10W-40		Multifleet SHPD 10W-40	
Check every 250 hours, change every 1000 hours			



use Normal		CLIMATE Cold
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 20W-20	HDX 20W-20	
Check every 250 hours, change every 10	00 hours	
use Normal		CLIMATE Arctic
PRODUCT RECOMMENDATION 1  Multifleet SCD 10W	PRODUCT RECOMMENDATION 2 HDX 10W	PRODUCT RECOMMENDATION 3  ATF Almirol
Check every 250 hours, change every 10	00 hours	
use Initial service		climate Mediterranean
PRODUCT RECOMMENDATION 1  Dieselfleet CD+ 15W-40	PRODUCT RECOMMENDATION 2  Multifleet SHPD 15W-40	
Change every 100 hours		
use Initial service		climate Moderate
PRODUCT RECOMMENDATION 1  Kroontrak MTH 10W-30	PRODUCT RECOMMENDATION 2 Synfleet SHPD 10W-40	PRODUCT RECOMMENDATION 3  Multifleet SHPD 10W-40
Change every 100 hours		
use Initial service		CLIMATE
PRODUCT RECOMMENDATION 1  Multifleet SCD 20W-20	PRODUCT RECOMMENDATION 2 HDX 20W-20	
Change every 100 hours		
use Initial service		climate Arctic
PRODUCT RECOMMENDATION 1  Multifleet SCD 10W	PRODUCT RECOMMENDATION 2 HDX 10W	PRODUCT RECOMMENDATION 3  ATF Almirol
Change every 100 hours	1	1
HYDRAULIC SYSTEM		
use Normal		CLIMATE  Moderate

PRODUCT RECOMMENDATION 2

Perlus H 68

Perlus H 46

PRODUCT RECOMMENDATION 1

Change every 2000 hours



HYDRAULIC BRAKE SYSTEM		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Drauliquid-S DOT 4		
Change every 4000 hours	·	

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.