

# BOBCAT TELESCOPIC HANDLERS

## T3071CD PERKINS 1004.42 (2000-2004)



**ENGINE** Perkins 1004.42  
Capacity: 6,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Dieselfleet CD+ 15W-40</b>	<b>Multifleet SHPD 15W-40</b>	

*Check every 10 hours, change every 600 hours*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Dieselfleet CD+ 15W-40</b>	<b>Multifleet SHPD 15W-40</b>	

*Change every 100 hours*

**DIFFERENTIAL FRONT**  
Capacity: 10,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Kroontrak CVT 10W-40</b>	<b>Agrifluid Synth XHP Ultra</b>	<b>Agrifluid HT-Plus</b>

*Check every 100 hours, change every 600 hours*

**DIFFERENTIAL REAR**  
Capacity: 10 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Kroontrak CVT 10W-40</b>	<b>Agrifluid Synth XHP Ultra</b>	<b>Agrifluid HT-Plus</b>

*Check every 100 hours, change every 600 hours*

**HUB REDUCTIONS FRONT**  
Capacity: 0,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Kroontrak CVT 10W-40</b>	<b>Agrifluid Synth XHP Ultra</b>	<b>Agrifluid HT-Plus</b>

*Check every 100 hours, change every 600 hours*

# BOBCAT TELESCOPIC HANDLERS

## T3071CD PERKINS 1004.42 (2000-2004)



### HUB REDUCTIONS REAR

Capacity: 0,7 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Kroontrak CVT 10W-40</b>	<b>Agrifluid Synth XHP Ultra</b>	<b>Agrifluid HT-Plus</b>

Check every 100 hours, change every 600 hours

### TRANSFERBOX

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Kroontrak CVT 10W-40</b>	<b>Agrifluid Synth XHP Ultra</b>	<b>Agrifluid HT-Plus</b>

### HYDRAULIC SYSTEM

Capacity: 70 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Perlus Biosynth 46</b>	<b>Perlus H 46</b>	

Check every 100 hours, change every 600 hours

### HYDRAULIC BRAKE SYSTEM

Capacity: 0,4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>LHM +</b>		

Check every 100 hours, change every 600 hours

### COOLING SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant -38 Organic NF</b>	<b>Coolant -26</b>	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.