

BOMAG SINGLE DRUM VIBRATORY ROLLERS BW BW-212D-3 DEUTZ BF6M- 1012E (S/N 101 580 35 1199 ->)



ENGINE Deutz BF6M-1012E
Capacity: 17,5 liter

| USE | CLIMATE |
|----------------------------------|----------|
| Normal, fuel sulfur level <0,5 % | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|-----------------------------|-----------------------------|-------------------------------|
| Kroontrak CVT 10W-40 | Synfleet SHPD 10W-40 | Dieselfleet CD+ 15W-40 |

Check every 10 hours, change every 500 hours/ 12 months

| USE | CLIMATE |
|-----------------|----------|
| Initial service | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|-----------------------------|-----------------------------|-------------------------------|
| Kroontrak CVT 10W-40 | Synfleet SHPD 10W-40 | Dieselfleet CD+ 15W-40 |

Change every 50 hours

DIFFERENTIAL

Capacity: 12,5 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|-----------------------------|------------------------------------|--|
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |

Check every 250 hours, change every 1000 hours/ 12 months

| USE | CLIMATE |
|-----------------|----------|
| Initial service | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|-----------------------------|------------------------------------|--|
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |

Change every 50 hours

HUB REDUCTIONS

Capacity: 1,8 liter (each side)

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|-----------------------------|------------------------------------|--|
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |

Check every 250 hours, change every 1000 hours/ 12 months

| USE | CLIMATE |
|-----------------|----------|
| Initial service | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|-----------------------------|------------------------------------|--|
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |

Change every 50 hours

BOMAG SINGLE DRUM VIBRATORY ROLLERS BW BW-212D-3 DEUTZ BF6M- 1012E (S/N 101 580 35 1199 ->)

**HYDRAULIC SYSTEM**

Capacity: 60 liter

| USE | | CLIMATE |
|--------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Perlus H 46 | | |

Check every 10 hours, change every 2000 hours/ 24 months

GREASE POINTS/NIPPLES

| USE | | CLIMATE |
|--------------------------|---------------------------------|------------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

COOLING SYSTEM

Capacity: 20 liter

| USE | | CLIMATE |
|-------------------------------|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Coolant -38 Organic NF | Coolant -26 | |

Check every 250 hours, change every 2000 hours/ 24 months

VIBRATORY BEARINGS

Capacity: 0,8 liter (each side)

| USE | | CLIMATE |
|-------------------------------|-------------------------------|-------------------------------|
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agridiesel CRD+ 15W-40 | Dieselfleet CD+ 15W-40 | Multifleet SHPD 15W-40 |

Check every 250 hours, change every 2000 hours/ 24 months

| USE | | CLIMATE |
|-------------------------------|-------------------------------|-------------------------------|
| Initial service | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agridiesel CRD+ 15W-40 | Dieselfleet CD+ 15W-40 | Multifleet SHPD 15W-40 |

Change every 500 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.