

BOMAG TANDEM VIBRATORY ROLLERS

BW-AD/SL BW-125AD-4 KUBOTA D1703-M-DI (2004-2008)



ENGINE Kubota D1703-M-DI
Capacity: 6,5 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Multifleet SCD 30

Check every 10 hours, change every 250 hours/ 12 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Kroontrak CVT 10W-40

PRODUCT RECOMMENDATION 2

Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 3

Kroontrak MTH 10W-30

Check every 10 hours, change every 250 hours/ 12 months

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

Multifleet SCD 10W

Check every 10 hours, change every 250 hours/ 12 months

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1

Multifleet SCD 30

Check every 10 hours, change every 50 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

Kroontrak CVT 10W-40

PRODUCT RECOMMENDATION 2

Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 3

Kroontrak MTH 10W-30

Check every 10 hours, change every 50 hours

USE	CLIMATE
Initial service	Arctic

PRODUCT RECOMMENDATION 1

Multifleet SCD 10W

Check every 10 hours, change every 50 hours

BOMAG TANDEM VIBRATORY ROLLERS

BW-AD/SL BW-125AD-4 KUBOTA D1703-M-DI (2004-2008)

**HYDRAULIC SYSTEM**

Capacity: 28 liter (Hydraulic tank)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus Biosynth 46	Perlus H 46	

Check every 10 hours, change every 2000 hours/ 24 months

COOLING SYSTEM

Capacity: 4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Check every 10 hours, change every 2000 hours/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.