

# BOMAG TANDEM VIBRATORY ROLLERS

## BW-AD/SL BW-161ADCV DEUTZ BF4M 2011

(2005-2008)



**ENGINE** Deutz BF4M-2011  
Capacity: 10 liter

USE	CLIMATE
Extended, fuel sulfur level <0,5 %, ambient temperature > -10°C	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Kroontrak CVT 10W-40</b>	<b>Agrisynth MSP 10W-40</b>	<b>Agridiesel MSP 15W-40</b>

*Check every 10 hours, change every 500 hours/ 12 months*

USE	CLIMATE
Normal, fuel sulfur level <0,5 %, ambient temperature > -10°C	Tropical

PRODUCT RECOMMENDATION 1		
<b>Multifleet SCD 40</b>		

*Check every 10 hours, change every 250 hours/ 12 months*

USE	CLIMATE
Normal, fuel sulfur level <0,5 %, ambient temperature > -10°C	Mediterranean

PRODUCT RECOMMENDATION 1		
<b>Multifleet SCD 30</b>		

*Check every 10 hours, change every 250 hours/ 12 months*

USE	CLIMATE
Normal, fuel sulfur level <0,5 %, ambient temperature > -10°C	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Kroontrak CVT 10W-40</b>	<b>Agridiesel CRD+ 15W-40</b>	<b>Kroontrak MTH 10W-30</b>

*Check every 10 hours, change every 250 hours/ 12 months*

USE	CLIMATE
Normal, fuel sulfur level <0,5 %, ambient temperature > -10°C	Cold

PRODUCT RECOMMENDATION 1		
<b>Multifleet SCD 20W-20</b>		

*Check every 10 hours, change every 250 hours/ 12 months*

USE	CLIMATE
Normal, fuel sulfur level <0,5 %, ambient temperature > -10°C	Arctic

PRODUCT RECOMMENDATION 1		
<b>Multifleet SCD 10W</b>		

*Check every 10 hours, change every 250 hours/ 12 months*

# BOMAG TANDEM VIBRATORY ROLLERS

## BW-AD/SL BW-161ADCV DEUTZ BF4M 2011

(2005-2008)

**EXCITER SHAFT TUBE**

Capacity: 6,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Dieselfleet CD+ 15W-40</b>	<b>Multifleet SHPD 15W-40</b>	

*Change every 1000 hours*

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Dieselfleet CD+ 15W-40</b>	<b>Multifleet SHPD 15W-40</b>	

*Change every 250 hours*

USE		CLIMATE
Second change only		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Dieselfleet CD+ 15W-40</b>	<b>Multifleet SHPD 15W-40</b>	

*Change every 500 hours***HYDRAULIC SYSTEM**

Capacity: 60 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Perlus Biosynth 46</b>	<b>Perlus H 46</b>	

*Check every 10 hours, change every 2000 hours/ 24 months*

USE		CLIMATE
Biodegradable oil		Moderate
PRODUCT RECOMMENDATION 1		
<b>Perlus Biosynth 46</b>		

*Check every 10 hours, change every 2000 hours/ 24 months***GREASE POINTS/NIPPLES OSCILLATING ARTICULATED JOINTS**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

*Check every 10 hours, change every 2000 hours/ 24 months*

# BOMAG TANDEM VIBRATORY ROLLERS

## BW-AD/SL BW-161ADCV DEUTZ BF4M 2011

(2005-2008)

**DRUM DRIVE UNIT**

Capacity: 1,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	

*Change every 1000 hours*

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	

*Change every 250 hours*

USE		CLIMATE
Second change only		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	

*Change every 500 hours***STEERING CHAINS**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.