

## CASE TRACKED LOADERS 455C

**ENGINE** Case 4-390

| USE                           |                               | CLIMATE  |
|-------------------------------|-------------------------------|----------|
| Normal                        |                               | Moderate |
| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2      |          |
| <b>Dieselfleet CD+ 15W-40</b> | <b>Multifleet SHPD 15W-40</b> |          |
| <i>Change every 250 hours</i> |                               |          |

**TRANSMISSION + TORQUE CONVERTER**

| USE                              |                          | CLIMATE  |
|----------------------------------|--------------------------|----------|
| Normal                           |                          | Moderate |
| PRODUCT RECOMMENDATION 1         | PRODUCT RECOMMENDATION 2 |          |
| <b>Agrifluid Synth XHP Ultra</b> | <b>Agrifluid HT-Plus</b> |          |
| <i>Change every 1000 hours</i>   |                          |          |

**HYDRAULIC SYSTEM**

| USE                              |                          | CLIMATE  |
|----------------------------------|--------------------------|----------|
| Normal                           |                          | Moderate |
| PRODUCT RECOMMENDATION 1         | PRODUCT RECOMMENDATION 2 |          |
| <b>Agrifluid Synth XHP Ultra</b> | <b>Agrifluid HT-Plus</b> |          |
| <i>Change every 1000 hours</i>   |                          |          |

**HYDRAULIC BRAKE SYSTEM**

| USE                              |                          | CLIMATE                  |
|----------------------------------|--------------------------|--------------------------|
| Normal                           |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1         | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| <b>Agrifluid Synth XHP Ultra</b> | <b>Agrifluid HT-Plus</b> | <b>ATF Dexron II-D</b>   |

**GREASE POINTS/NIPPLES**

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>MoS2 Grease EP 2</b>  |  |          |

**DRIVE CHAIN COMPARTMENTS**

We are unable to give a standard recommendation for this component. Please contact our service department.

**CASE TRACKED LOADERS 455C**

| WINCH   |  |                     |
|---|--|---------------------|
| USE<br>Normal   |  | CLIMATE<br>Moderate |
| PRODUCT RECOMMENDATION 1<br><b>Gearlube GL-4 80W-90</b> | PRODUCT RECOMMENDATION 2<br><b>Unigear HS GL-3/GL-5 80W-90</b> |                     |
| <i>Change every 1000 hours</i>                          |  |                     |

| WINCH CONTROL  |   |                     |
|--|---|---------------------|
| USE<br>Normal  |   | CLIMATE<br>Moderate |
| PRODUCT RECOMMENDATION 1<br><b>Drauliquid-LV Super DOT 4</b> | PRODUCT RECOMMENDATION 2<br><b>Drauliquid-S DOT 4</b> |                     |

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*