

# CASE SKID STEER LOADERS 1830 (1974-1980)



## ENGINE Leyland

| USE                           |                               | CLIMATE       |
|-------------------------------|-------------------------------|---------------|
| Normal                        |                               | Mediterranean |
| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2      |               |
| <b>Dieselfleet CD+ 15W-40</b> | <b>Multifleet SHPD 15W-40</b> |               |

*Change every 100 hours*

## HYDRAULIC SYSTEM

| USE                              |                          | CLIMATE  |
|----------------------------------|--------------------------|----------|
| Normal                           |                          | Moderate |
| PRODUCT RECOMMENDATION 1         | PRODUCT RECOMMENDATION 2 |          |
| <b>Agrifluid Synth XHP Ultra</b> | <b>Agrifluid HT-Plus</b> |          |

*Change every 1000 hours*

## GREASE POINTS/NIPPLES

| USE                             |                                | CLIMATE  |
|---------------------------------|--------------------------------|----------|
| Normal                          |                                | Moderate |
| PRODUCT RECOMMENDATION 1        | PRODUCT RECOMMENDATION 2       |          |
| <b>Q7 MP Calcep Grease WR 2</b> | <b>Caliplex HD Grease EP 2</b> |          |

## DRIVE CHAIN COMPARTMENTS

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>HDX 30</b>            |  |          |

*Change every 500 hours*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*