

CASE SKID STEER LOADERS SV250 (2012-2019)



ENGINE Case 434T/E Tier 4
Capacity: 9,5 liter

USE Normal		CLIMATE Moderate
---------------	--	---------------------

PRODUCT RECOMMENDATION 1 Agridiesel CRD+ 15W-40	PRODUCT RECOMMENDATION 2 Armado Synth 5W-30	PRODUCT RECOMMENDATION 3 Dieselfleet LSP Ultra 10W-30
---	---	---

Check every 10 hours, change every 250 hours

USE Initial service		CLIMATE Moderate
------------------------	--	---------------------

PRODUCT RECOMMENDATION 1 Agridiesel CRD+ 15W-40	PRODUCT RECOMMENDATION 2 Armado Synth 5W-30	PRODUCT RECOMMENDATION 3 Dieselfleet LSP Ultra 10W-30
---	---	---

Change every 50 hours

CHAIN DRIVE UNIT
Capacity: 27,9 liter (each)

USE Normal		CLIMATE Moderate
---------------	--	---------------------

PRODUCT RECOMMENDATION 1 Kroontrak MTH 10W-30	PRODUCT RECOMMENDATION 2 Armado Synth 5W-30	PRODUCT RECOMMENDATION 3 Dieselfleet LSP Ultra 10W-30
---	---	---

Check every 500 hours, change every 1000 hours

HYDRAULIC SYSTEM
Capacity: 15 liter (Hydraulic tank), Capacity: 44,5 liter (System)

USE Normal		CLIMATE Moderate
---------------	--	---------------------

PRODUCT RECOMMENDATION 1 Kroontrak MTH 10W-30	PRODUCT RECOMMENDATION 2 Armado Synth 5W-30	PRODUCT RECOMMENDATION 3 Dieselfleet LSP Ultra 10W-30
---	---	---

Check every 10 hours, change every 1000 hours

GREASE POINTS/NIPPLES

USE Normal		CLIMATE Moderate
---------------	--	---------------------

PRODUCT RECOMMENDATION 1 MoS2 Grease EP 2		
---	--	--

Change every 10 hours

CASE SKID STEER LOADERS SV250 (2012-2019)



COOLING SYSTEM

Capacity: 19 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Check every 10 hours, change every 1000 hours

TRAVEL REDUCTION UNIT

Capacity: 1 liter (each)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Change every 500 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Change every 50 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.