

CATERPILLAR ASPHALT PAVERS AP/BG

AP-655D GNN, GNZ



ENGINE C6.6 Acert
Capacity: 14 liter

USE
Normal

CLIMATE
Mediterranean

PRODUCT RECOMMENDATION 1
Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 2
Dieselfleet CD+ 15W-40

PRODUCT RECOMMENDATION 3
Multifleet SHPD 15W-40

Change every 250 hours

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Agrisynth LSP 10W-40

PRODUCT RECOMMENDATION 2
Kroontrak CVT 10W-40

PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30

Change every 250 hours

HUB REDUCTIONS

Capacity: 4,3 liter (each hub)

USE
Normal

CLIMATE
Mediterranean

PRODUCT RECOMMENDATION 1
Gear Oil Alcat 50

Change every 500 hours

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Abacot MEP HD 220

Change every 500 hours

PUMP DRIVE HYDROSTATIC TRANSMISSION

Capacity: 2,8 liter

USE
Normal

CLIMATE
Mediterranean

PRODUCT RECOMMENDATION 1
Gear Oil Alcat 50

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Abacot MEP HD 220

CATERPILLAR ASPHALT PAVERS AP/BG

AP-655D GNN, GNZ



HYDRAULIC SYSTEM

Capacity: 238 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 30*Change every 1000 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Kroontrak CVT 10W-40

PRODUCT RECOMMENDATION 2

Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 3

Agrifluid HT-Plus*Change every 1000 hours*

USE	CLIMATE
Biodegradable oil	Moderate

PRODUCT RECOMMENDATION 1

Perlus Biosynth 46

COOLING SYSTEM

Capacity: 30 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 17*Change every 12000 hours/ 72 months*

REDUCTION UNITS AUGER ASSEMBLY AND CONVEYOR(S)

Capacity: 0,6 liter (each side)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Gearlube GL-5 85W-140

PRODUCT RECOMMENDATION 2

Unigear LS GL-3/GL-5 85W-140*Change every 500 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube Racing 75W-140

PRODUCT RECOMMENDATION 2

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 3

Unigear HS GL-3/GL-5 80W-90*Change every 500 hours*

CATERPILLAR ASPHALT PAVERS AP/BG AP-655D GNN, GNZ

**TRACK ROLLERS**

Capacity: 160 CM3

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Multifleet SCD 40*Check every 500 hours, change every 2000 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Multifleet SCD 30*Check every 500 hours, change every 2000 hours*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.