

AFTER)

ENGINE C6.6 Acert		
Capacity: 17 liter		
JSE		CLIMATE
Preferred, fuel sulfur level < 0,1%		Mediterranean
PRODUCT RECOMMENDATION 1 Agridiesel MSP 15W-40	PRODUCT RECOMMENDATION 2 Dieselfleet MSP 15W-40	
Check every 10 hours, change every 500) hours	
USE		CLIMATE
Preferred, fuel sulfur level < 0,1%		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30	
Check every 10 hours, change every 500) hours	
USE		CLIMATE
Alternative, fuel sulfur level <0,1%		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrisynth MSP 10W-40	Dieselfleet MSP 15W-40	
Check every 10 hours, change every 500) hours	
USE		CLIMATE
Alternative, fuel sulfur level <0,1%		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra FE 5W-30	Agridiesel MSP 15W-40	Dieselfleet LSP Ultra 10W-30
Check every 10 hours, change every 500) hours	
USE		CLIMATE
Fuel sulfur level >0,1%, flexible (flu	id analysis)	Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agridiesel MSP 15W-40	Dieselfleet MSP 15W-40	
Check every 250 hours		
USE		CLIMATE
Fuel sulfur level >0,1%, flexible (flu	id analysis)	Moderate
	PRODUCT RECOMMENDATION 2	
PRODUCT RECOMMENDATION 1	T RODGOT REGOMMENDATION 2	
PRODUCT RECOMMENDATION 1 Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30	



AFTER)

DIFFERENTIAL FRONT Capacity: 11 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT
Check every 1 months/ 250 hours, change	e every 12 months/ 2000 hours	
USE		CLIMATE
> 25% Travel		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT
Check every 1 months/ 250 hours, change	e every 12 months/ 1500 hours	

DIFFERENTIAL REAR Capacity: 14,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT
Check every 1 months/ 250 hours, change	e every 12 months/ 2000 hours	
USE		CLIMATE
> 25% Travel		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT
Check every 1 months/ 250 hours, change	e every 12 months/ 1500 hours	

Capacity: 2,5 liter (each)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT
Check every 1 months/ 250 hours, of	change every 12 months/ 2000 hours	
USE		CLIMATE
> 25% Travel		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT
Check every 1 months/ 250 hours, of	change every 12 months/ 1500 hours	

HUB REDUCTIONS FRONT



AFTER)

HUB REDUCTIONS REAR Capacity: 2,5 liter (each)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT
Check every 1 months/ 250 hours, change	e every 12 months/ 2000 hours	
USE		CLIMATE
> 25% Travel		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT
Check every 1 months/ 250 hours, change	e every 12 months/ 1500 hours	

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	
Check every 1 months/ 250 hours,	change every 12 months/ 2000 hours	·
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Check every 1 months/ 250 hours,	change every 12 months/ 2000 hours	
USE		CLIMATE
> 25% Travel		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	
Check every 1 months/ 250 hours,	change every 12 months/ 1500 hours	
USE		CLIMATE
> 25% Travel		Cold
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		



AFTER)

HYDRAULIC SYSTEM Capacity: 170 liter (Hydraulic tank), Capac	ity: 255 liter (System)	
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		
Check every 10 hours, change every 2000	hours/ 12 months	_
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Agrifluid HT-Plus	Kroontrak MTH 10W-30
Check every 10 hours, change every 2000	hours/ 12 months	
USE		CLIMATE
Biodegradable oil		Moderate
PRODUCT RECOMMENDATION 1		
Perlus Biosynth 46		
Check every 10 hours, change every 2000	hours/ 12 months	

Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Alternative (acceptable)		Moderate
USE		CLIMATE
MoS2 Grease EP 2		
PRODUCT RECOMMENDATION 1		
Normal		Moderate
USE		CLIMATE
GREASE POINTS/NIPPLES		

PRODUCT RECOMMENDATION

CATERPILLAR WHEELED MATERIAL HANDLERS M318D MH D9X (2007 AND



AFTER)

COOLING SYSTEM Capacity: 36 liter		
USE		CLIMATE
Preferred, extended		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 17		
Check every 10 hours, change every 72 m	onths/ 12000 hours	
USE		CLIMATE
Alternative (acceptable)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF
Check every 10 hours, change every 36 m	onths/ 3000 hours	

SWING GEAR Capacity: 9 kg	
USE	CLIMATE
Alternative (acceptable)	Moderate
PRODUCT RECOMMENDATION 1	
MoS2 Grease EP 2	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.