

ENGINE C9 Acert Capacity: 28 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Kroontrak MTH 10W-30	Asyntho 5W-30

Check every 10 hours, change every 3 months/ 500 hours

FINAL DRIVES Capacity: 13,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 50		
Charle avery 1 months/250 hours change	avery 12 months/2000 hours	

Check every 1 months/250 hours, change every 12 months/2000 hours

USE	CLIMATE
Normal	Cold
PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 30	

Check every 1 months/ 250 hours, change every 12 months/ 2000 hours

USE		CLIMATE
Severe		Cold
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	
Check every 1 months/ 250 hours, change every 12 months/ 2000 hours		

TRANSMISSION Capacity: 148 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	

Check every 10 hours, change every 6 months/ 1000 hours

USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Check every 10 hours change every 6 mo	nths/ 1000 hours	



HYDRAULIC SYSTEM Capacity: 47,3 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 30	Gear Oil Alcat 30	
Check every 10 hours, change every 2000	hours/ 12 months	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Agrifluid HT-Plus	Kroontrak MTH 10W-30
Check every 10 hours, change every 2000	hours/ 12 months	
USE		CLIMATE
Biodegradable oil		Moderate
PRODUCT RECOMMENDATION 1		
Perlus Biosynth 46		

Check every 10 hours, change every 2000 hours/ 12 months

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		
USE		CLIMATE
Light Duty		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	

Labora Grease

COOLING SYSTEM Capacity: 70 liter		
use Normal		climate Moderate
PRODUCT RECOMMENDATION 1 Coolant SP 17		
Check every 10 hours, change every 72 m	onths/ 12000 hours	

HT Q9 High Grade Grease



PIVOT SHAFTS Capacity: 5 liter	
USE	CLIMATE
Normal	Mediterranean
PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 50	
Check every 1 months/ 250 hours	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 30	
Check every 1 months/ 250 hours	
USE	CLIMATE
Normal	Arctic
PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 10W	
Check every 1 months/ 250 hours	

RECOIL SPRING COMPARTMENT Capacity: 25 liter	
USE	CLIMATE
Normal	Mediterranean
PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 50	
Oh	

Check every 3 months/ 500 hours

use Normal	climate Moderate
PRODUCT RECOMMENDATION 1 Gear Oil Alcat 30	

Check every 3 months/ 500 hours

use Normal	climate Arctic
PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 10W	
Check every 3 months/ 500 hours	



WINCH HYDRAULIC DRIVE Capacity: 67,2 liter				
USE		CLIMATE		
Normal		Mediterranean		
PRODUCT RECOMMENDATION 1				
Gear Oil Alcat 30				
Check every 1 months/ 250 hours, change every 6 months/ 1000 hours				
USE		CLIMATE		
Normal		Cold		
PRODUCT RECOMMENDATION 1				

Gear Oil Alcat 10W

Check every 1 months/ 250 hours, change every 6 months/ 1000 hours

WINCH MECHANICAL DRIVE Capacity: 67,2 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	

Check every 1 months/ 250 hours, change every 6 months/ 1000 hours

USE		CLIMATE		
Normal		Cold		
PRODUCT RECOMMENDATION 1				
Gear Oil Alcat 10W				
Check every 1 months/ 250 hours, change every 6 months/ 1000 hours				

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.