

ENGINE 3054E ATAAC Capacity: 9 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Kroontrak MTH 10W-30	Asyntho 5W-30

Check every 10 hours, change every 3 months/ 500 hours

BOGIE REAR Capacity: 50 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 50		
Check every 3 months/ 500 hours, change	every 12 months/ 2000 hours	
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		
Check every 3 months/ 500 hours, change	every 12 months/ 2000 hours	
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Check every 3 months/ 500 hours, change	every 12 months/ 2000 hours	



DIFFERENTIAL FRONT		
DIFFERENTIAL FRONT Capacity: 11 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 50		
Check every 3 months/ 500 hours, change	e every 12 months/ 2000 hours	
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		
Check every 3 months/ 500 hours, change	every 12 months/ 2000 hours	
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Check every 3 months/ 500 hours, change	every 12 months/ 2000 hours	
DIFFERENTIAL REAR Capacity: 11 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 50		
Check every 3 months/ 500 hours, change	every 12 months/ 2000 hours	
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		
Check every 3 months/ 500 hours, change	e every 12 months/ 2000 hours	
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Check every 3 months/ 500 hours, change		
Check every 3 months, 500 nours, change	every 12 months/ 2000 hours	



TRANSMISSION		
Capacity: 4,5 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	
Check every 10 hours, change every 1000	0 hours/ 12 months	
USE		CLIMATE
Normal	,	Cold
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Check every 10 hours, change every 1000	0 hours/ 12 months	
USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	
Change every 250 hours		
USE		CLIMATE
use Initial service		CLIMATE
Initial service		
Initial service PRODUCT RECOMMENDATION 1		
Initial service PRODUCT RECOMMENDATION 1 Gear Oil Alcat 10W		
Initial service PRODUCT RECOMMENDATION 1 Gear Oil Alcat 10W Change every 250 hours HYDRAULIC SYSTEM		
Initial service PRODUCT RECOMMENDATION 1 Gear Oil Alcat 10W Change every 250 hours		
Initial service PRODUCT RECOMMENDATION 1 Gear Oil Alcat 10W Change every 250 hours HYDRAULIC SYSTEM Capacity: 95 liter (Hydraulic tank) USE		Cold
Initial service PRODUCT RECOMMENDATION 1 Gear Oil Alcat 10W Change every 250 hours HYDRAULIC SYSTEM Capacity: 95 liter (Hydraulic tank) USE Normal		Cold
Initial service PRODUCT RECOMMENDATION 1 Gear Oil Alcat 10W Change every 250 hours HYDRAULIC SYSTEM Capacity: 95 liter (Hydraulic tank) USE Normal PRODUCT RECOMMENDATION 1		Cold
Initial service PRODUCT RECOMMENDATION 1 Gear Oil Alcat 10W Change every 250 hours HYDRAULIC SYSTEM Capacity: 95 liter (Hydraulic tank) USE Normal PRODUCT RECOMMENDATION 1 Gear Oil Alcat 30		Cold
Initial service PRODUCT RECOMMENDATION 1 Gear Oil Alcat 10W Change every 250 hours HYDRAULIC SYSTEM Capacity: 95 liter (Hydraulic tank) USE Normal PRODUCT RECOMMENDATION 1	0 hours/ 12 months	Cold
Initial service PRODUCT RECOMMENDATION 1 Gear Oil Alcat 10W Change every 250 hours HYDRAULIC SYSTEM Capacity: 95 liter (Hydraulic tank) USE Normal PRODUCT RECOMMENDATION 1 Gear Oil Alcat 30 Check every 10 hours, change every 2006 USE	0 hours/ 12 months	CLIMATE Mediterranean
Initial service PRODUCT RECOMMENDATION 1 Gear Oil Alcat 10W Change every 250 hours HYDRAULIC SYSTEM Capacity: 95 liter (Hydraulic tank) USE Normal PRODUCT RECOMMENDATION 1 Gear Oil Alcat 30 Check every 10 hours, change every 2000	0 hours/ 12 months	CLIMATE Mediterranean
Initial service PRODUCT RECOMMENDATION 1 Gear Oil Alcat 10W Change every 250 hours HYDRAULIC SYSTEM Capacity: 95 liter (Hydraulic tank) USE Normal PRODUCT RECOMMENDATION 1 Gear Oil Alcat 30 Check every 10 hours, change every 2006 USE	O hours/ 12 months PRODUCT RECOMMENDATION 2 Agrifluid HT-Plus	CLIMATE Mediterranean CLIMATE

Check every 10 hours, change every 2000 hours/ 12 months



GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

COOLING SYSTEM Capacity: 26 liter		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Coolant SP 17		

Check every 10 hours, change every 72 months/ 12000 hours

TRANSFERBOX LOG LOADER Capacity: 4 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 10 hours, change every 6 months/ 1000 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Change every 100 hours		

Change every 100 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.