

ENGINE 3516B Capacity: 291 liter		
USE		CLIMATE
Normal (preferred)		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40
Check every 10 hours, change every	1 months/ 250 hours	
USE		CLIMATE
Normal (preferred)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrisynth LSP 10W-40	Multifleet SHPD 10W-40	
Check every 10 hours, change every	1 months/ 250 hours	
USE		CLIMATE
Alternative (acceptable)		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agridiesel CRD+ 15W-40	Multifleet SHPD 15W-40	
Check every 10 hours, change every	1 months/ 250 hours	
USE		CLIMATE
Alternative (acceptable)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 10W-40
Check every 10 hours, change every	1 months/ 250 hours	

#### CATERPILLAR FRONT SHOVEL 5230B 4HZ



(2001-2004)

HYDRAULIC SYSTEM Capacity: 1660 liter (Hydraulic tank), Capa	city: 2100 liter (System)	
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 30	Gear Oil Alcat 30	
Check every 10 hours, change every 1000	) hours/ 12 months	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Agrifluid HT-Plus	Kroontrak MTH 10W-30
Check every 10 hours, change every 1000	) hours/ 12 months	
USE		CLIMATE
Biodegradable oil		Moderate
PRODUCT RECOMMENDATION 1		
Perlus Biosynth 46		
Check every 10 hours, change every 1000	) hours/ 12 months	

#### **GREASE POINTS/NIPPLES**

We are unable to give a standard recommendation for this component. Please contact our service department.

COOLING SYSTEM Capacity: 500 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 17		
Check every 10 hours, change every 72 n	onths/ 6000 hours	

CARRIER ROLLERS Capacity: 0,7 liter (each)	
USE	CLIMATE
Normal	Mediterranean
PRODUCT RECOMMENDATION 1	
Multifleet SCD 40	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Multifleet SCD 30	



USE		CLIMATE	
Initial service		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Gear Oil Alcat 30	Gear Oil Alcat 50		
Change every 250 hours/ 6 months			
USE		CLIMATE	
Initial service		Arctic	
PRODUCT RECOMMENDATION 1			
Gear Oil Alcat 10W			
Change every 250 hours/ 6 months			
USE		CLIMATE	
Flexible, fluid analysis		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Gear Oil Alcat 30	Gear Oil Alcat 50		
Check every 1 months/ 250 hours, o	hange every 6 months/ 1000 hours		
USE		CLIMATE	
Flexible, fluid analysis		Arctic	
PRODUCT RECOMMENDATION 1			
Gear Oil Alcat 10W			
	hange every 6 months/ 1000 hours		

PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
	Moderate
	CLIMATE
	PRODUCT RECOMMENDATION 2



USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	
Change every 250 hours/ 6 months		
USE		CLIMATE
Initial service		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Change every 250 hours/ 6 months		
USE		CLIMATE
Flexible, fluid analysis		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	
Check every 1 months/ 250 hours, of	change every 6 months/ 1000 hours	
USE		CLIMATE
Flexible, fluid analysis		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Check every 1 months/ 250 hours, of	change every 6 months/ 1000 hours	
TRACK IDLERS		
Capacity: 6 liter (each)		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SCD 40		
USE		CLIMATE

Normal

PRODUCT RECOMMENDATION 1

Multifleet SCD 30

Moderate



TRACK ROLLERS
Capacity: 2 liter (each)

USE
Normal

PRODUCT RECOMMENDATION 1

Multifleet SCD 40

CLIMATE
Moderate

Moderate

PRODUCT RECOMMENDATION 1

Multifleet SCD 30

Capacity: 2 liter (each)			
USE		CLIMATE	
Initial service		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Gear Oil Alcat 30	Gear Oil Alcat 50		
Change every 250 hours/ 6 months	8		
USE		CLIMATE	
Initial service		Arctic	
PRODUCT RECOMMENDATION 1			
Gear Oil Alcat 10W			
Change every 250 hours/ 6 months	5	·	
USE		CLIMATE	
Flexible, fluid analysis		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Gear Oil Alcat 30	Gear Oil Alcat 50		
Check every 1 months/ 250 hours,	change every 6 months/ 1000 hours		
USE		CLIMATE	
Flexible, fluid analysis		Arctic	
PRODUCT RECOMMENDATION 1			
Gear Oil Alcat 10W			



TRAVEL REDUCTION UNIT PLANETARY GEAR Capacity: 80 liter (each) CLIMATE USE Initial service Moderate PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 1 **Gear Oil Alcat 30 Gear Oil Alcat 50** Change every 250 hours/ 6 months USE CLIMATE Initial service Arctic PRODUCT RECOMMENDATION 1 **Gear Oil Alcat 10W** Change every 250 hours/ 6 months CLIMATE Flexible, fluid analysis Moderate PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 **Gear Oil Alcat 30 Gear Oil Alcat 50** Check every 1 months/ 250 hours, change every 6 months/ 1000 hours CLIMATE Flexible, fluid analysis Arctic PRODUCT RECOMMENDATION 1 **Gear Oil Alcat 10W** Check every 1 months/ 250 hours, change every 6 months/ 1000 hours



TRAVEL REDUCTION UNIT SPUR GEAR Capacity: 11 liter (each) CLIMATE USE Initial service Moderate PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 **Gear Oil Alcat 30 Gear Oil Alcat 50** Change every 250 hours/ 6 months USE CLIMATE Initial service Arctic PRODUCT RECOMMENDATION 1 **Gear Oil Alcat 10W** Change every 250 hours/ 6 months CLIMATE Flexible, fluid analysis Moderate PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 **Gear Oil Alcat 30 Gear Oil Alcat 50** Check every 1 months/ 250 hours, change every 6 months/ 1000 hours CLIMATE Flexible, fluid analysis Arctic PRODUCT RECOMMENDATION 1 **Gear Oil Alcat 10W** Check every 1 months/ 250 hours, change every 6 months/ 1000 hours

#### **CATERPILLAR FRONT SHOVEL 5230B 4HZ**



(2001-2004)

TRAVEL REDUCTION UNIT TRAVEL B Capacity: 0,3 liter (each)	RAKE		
USE		CLIMATE	
Initial service		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Gear Oil Alcat 30	Gear Oil Alcat 50		
Change every 250 hours/ 6 months			
USE		CLIMATE	
Initial service		Arctic	
PRODUCT RECOMMENDATION 1			
Gear Oil Alcat 10W			
Change every 250 hours/ 6 months			
USE		CLIMATE	
Flexible, fluid analysis		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Gear Oil Alcat 30	Gear Oil Alcat 50		
Check every 1 months/ 250 hours, change	e every 6 months/ 1000 hours		
USE		CLIMATE	
Flexible, fluid analysis		Arctic	
PRODUCT RECOMMENDATION 1			
Gear Oil Alcat 10W			
Check every 1 months/ 250 hours, change	ue every 6 months/ 1000 hours		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.