

CATERPILLAR FORKLIFT TRUCKS, GAS/LPG/PETROL GP18 MITSUBISHI 4G63 (1993-1999)

**ENGINE (PETROL) Mitsubishi 4G63**

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|-----------------------------|-------------------------------|--|
| Kroontrak MTH 10W-30 | Multifleet SHPD 15W-40 | |

Change every 1 months/ 200 hours

DIFFERENTIAL

| USE | CLIMATE |
|--------|---------------|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|-----------------------------|------------------------------------|--|
| Gearlube GL-4 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |

Change every 6 months/ 1200 hours

| USE | CLIMATE |
|--------|---------|
| Normal | Arctic |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|--------------------------|--------------------------|--------------------------|
| Agrifluid HT-Plus | SP Gear 5015 | Gearlube GL-4 80W |

Change every 6 months/ 1200 hours

TRANSFERBOX

| USE | CLIMATE |
|--------|---------------|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|-----------------------------|------------------------------------|--|
| Gearlube GL-4 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |

Change every 6 months/ 1200 hours

| USE | CLIMATE |
|--------|---------|
| Normal | Arctic |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|--------------------------|--------------------------|--------------------------|
| Agrifluid HT-Plus | SP Gear 5015 | Gearlube GL-4 80W |

Change every 6 months/ 1200 hours

TRANSMISSION Powershift

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|--------------------------|--|--|
| ATF Dexron II-D | | |

Change every 6 months/ 1200 hours

CATERPILLAR FORKLIFT TRUCKS, GAS/LPG/PETROL GP18 MITSUBISHI 4G63 (1993-1999)



HYDRAULIC SYSTEM

| USE | CLIMATE |
|--------|---------------|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1 | | |
|--------------------------|--|--|
| Perlus H 32 | | |

Change every 12 months/ 2400 hours

| USE | CLIMATE |
|--------|---------|
| Normal | Arctic |

| PRODUCT RECOMMENDATION 1 | | |
|--------------------------|--|--|
| Perlus H 22 | | |

Change every 12 months/ 2400 hours

HYDRAULIC BRAKE/CLUTCH SYSTEM

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|----------------------------------|---------------------------|--------------------------|
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4 | Drauliquid DOT 3 |

Change every 12 months/ 2400 hours

GREASE POINTS/NIPPLES CHASSIS

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|--------------------------|--|--|
| Gear Grease EP 1 | | |

GREASE POINTS/NIPPLES WHEEL BEARINGS

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|--------------------------|---------------------------------|------------------------------|
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.