

# CATERPILLAR ARTICULATED DUMP TRUCKS 730 AGF (TILL 2007)

**ENGINE**

Capacity: 36 liter

**USE**

Normal

**CLIMATE**

Mediterranean

**PRODUCT RECOMMENDATION 1****Dieselfleet CD+ 15W-40****PRODUCT RECOMMENDATION 2****Multifleet SHPD 15W-40***Change every 250 hours***DIFFERENTIAL CENTRE**

Capacity: 46 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Gear Oil Alcat 50***Check every 500 hours, change every 2000 hours***DIFFERENTIAL FRONT**

Capacity: 41 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Gear Oil Alcat 50***Check every 500 hours, change every 2000 hours***DIFFERENTIAL REAR**

Capacity: 47 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Gear Oil Alcat 50***Check every 500 hours, change every 2000 hours***FINAL DRIVES**

Capacity: 5 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Gear Oil Alcat 50***Check every 500 hours, change every 2000 hours*

# CATERPILLAR ARTICULATED DUMP TRUCKS 730 AGF (TILL 2007)



## TRANSFERBOX

Capacity: 18 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

**Gear Oil Alcat 30***Check every 500 hours, change every 1000 hours*

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1

**Gear Oil Alcat 10W***Check every 500 hours, change every 1000 hours*

## TRANSMISSION + TORQUE CONVERTER

Capacity: 36 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

**Gear Oil Alcat 30***Check every 500 hours, change every 1000 hours*

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1

**Gear Oil Alcat 10W***Check every 500 hours, change every 1000 hours*

## COOLING SYSTEM

Capacity: 67 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Coolant SP 17**

# CATERPILLAR ARTICULATED DUMP TRUCKS 730 AGF (TILL 2007)



## HYDRAULIC SYSTEM STEERING + BRAKES

Capacity: 151 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Gear Oil Alcat 10W</b>		

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*