

CATERPILLAR WHEELED LOADERS 908

8BS/CATERPILLAR 3054 (1998-2004)



ENGINE Caterpillar 3054
Capacity: 7,3 liter

USE	CLIMATE
Preferred	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Agridiesel MSP 15W-40	Dieselfleet MSP 15W-40

Check every 10 hours, change every 500 hours/ 12 months

USE	CLIMATE
Preferred	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra FE 5W-30	Agrisynth LSP Ultra 10W-40	Agrisynth MSP 10W-40

Check every 10 hours, change every 500 hours/ 12 months

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Check every 10 hours, change every 500 hours/ 12 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Agrisynth LSP 10W-40	Multifleet SHPD 10W-40

Check every 10 hours, change every 500 hours/ 12 months

USE	CLIMATE
Alternative (acceptable)	Mediterranean

PRODUCT RECOMMENDATION 1	
Dieselfleet MSP 15W-40	

Check every 10 hours, change every 500 hours/ 12 months

USE	CLIMATE
Alternative (acceptable)	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra FE 5W-30	Agrisynth LSP Ultra 10W-40	Agrisynth MSP 10W-40

Check every 10 hours, change every 500 hours/ 12 months

DIFFERENTIAL FRONT

Capacity: 7,5 liter, Capacity: 0,5 liter (LS-additive)

We are unable to give a standard recommendation for this component. Please contact our service department.

CATERPILLAR WHEELED LOADERS 908

8BS/CATERPILLAR 3054 (1998-2004)

**DIFFERENTIAL REAR**

Capacity: 8 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Check every 6 months/ 250 hours, change every 12 months/ 1000 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube Racing 75W-140	SP Gear 1011	Syngear TDL 75W-90

Check every 6 months/ 250 hours, change every 12 months/ 1000 hours

DIFFERENTIAL REAR LIMITED SLIP

Capacity: 7,5 liter, Capacity: 0,5 liter (LS-additive)

We are unable to give a standard recommendation for this component. Please contact our service department.

HUB REDUCTIONS FRONT

Capacity: 1,5 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Check every 6 months/ 250 hours, change every 12 months/ 1000 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube Racing 75W-140	SP Gear 1011	Syngear TDL 75W-90

Check every 6 months/ 250 hours, change every 12 months/ 1000 hours

CATERPILLAR WHEELED LOADERS 908

8BS/CATERPILLAR 3054 (1998-2004)



HUB REDUCTIONS REAR

Capacity: 1,5 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Check every 6 months/ 250 hours, change every 12 months/ 1000 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube Racing 75W-140	SP Gear 1011	Syngear TDL 75W-90

Check every 6 months/ 250 hours, change every 12 months/ 1000 hours

TRANSMISSION HYDROSTATIC

Capacity: 1,4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Check every 6 months/ 250 hours, change every 12 months/ 1000 hours

HYDRAULIC SYSTEM

Capacity: 49 liter (Hydraulic tank)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Check every 10 hours, change every 2000 hours/ 12 months

COOLING SYSTEM

Capacity: 16 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 17		

Check every 10 hours, change every 48 months/ 6000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.