

# CATERPILLAR TRACKED EXCAVATORS

## 211B 6XG (1990-1994)

**ENGINE**

Capacity: 10 liter

| USE                      |                          | CLIMATE       |
|--------------------------|--------------------------|---------------|
| Normal                   |                          | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |               |
| <b>Multifleet SCD 40</b> | <b>Multifleet SCD 30</b> |               |

*Change every 250 hours/ 1 months*

| USE                           |                             | CLIMATE                     |
|-------------------------------|-----------------------------|-----------------------------|
| Normal                        |                             | Moderate                    |
| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2    | PRODUCT RECOMMENDATION 3    |
| <b>Agridiesel CRD+ 15W-40</b> | <b>Kroontrak MTH 10W-30</b> | <b>Synfleet SHPD 10W-40</b> |

*Change every 250 hours/ 1 months*

| USE                       |  | CLIMATE |
|---------------------------|--|---------|
| Normal                    |  | Cold    |
| PRODUCT RECOMMENDATION 1  |  |         |
| <b>Multifleet SCD 10W</b> |  |         |

*Change every 250 hours/ 1 months***FINAL DRIVES**

Capacity: 2 liter (each side)

| USE                          |                                     | CLIMATE       |
|------------------------------|-------------------------------------|---------------|
| Normal                       |                                     | Mediterranean |
| PRODUCT RECOMMENDATION 1     | PRODUCT RECOMMENDATION 2            |               |
| <b>Gearlube GL-5 85W-140</b> | <b>Unigear LS GL-3/GL-5 85W-140</b> |               |

*Change every 2000 hours/ 12 months*

| USE                      |                           | CLIMATE                     |
|--------------------------|---------------------------|-----------------------------|
| Normal                   |                           | Moderate                    |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2  | PRODUCT RECOMMENDATION 3    |
| <b>SP Gear 1011</b>      | <b>Syngear TDL 75W-90</b> | <b>Gearlube GL-5 80W-90</b> |

*Change every 2000 hours/ 12 months*

| USE                      |                          | CLIMATE |
|--------------------------|--------------------------|---------|
| Normal                   |                          | Arctic  |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |         |
| <b>SP Gear 5015</b>      | <b>SP Gear 1071</b>      |         |

*Change every 2000 hours/ 12 months*

# CATERPILLAR TRACKED EXCAVATORS

## 211B 6XG (1990-1994)



### HYDRAULIC SYSTEM

Capacity: 125 liter

| USE    | CLIMATE       |
|--------|---------------|
| Normal | Mediterranean |

PRODUCT RECOMMENDATION 1

**Gear Oil Alcat 30***Change every 2000 hours/ 12 months*

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Gear Oil Alcat 10W***Change every 2000 hours/ 12 months*

### GREASE POINTS/NIPPLES

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**MoS2 Grease EP 2**

### COOLING SYSTEM

Capacity: 30 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Coolant SP 17***Change every 24 months/ 3000 hours*

# CATERPILLAR TRACKED EXCAVATORS

## 211B 6XG (1990-1994)


**SWING REDUCTION UNIT**

Capacity: 6,7 liter

| USE                          |                                     | CLIMATE       |
|------------------------------|-------------------------------------|---------------|
| Normal                       |                                     | Mediterranean |
| PRODUCT RECOMMENDATION 1     | PRODUCT RECOMMENDATION 2            |               |
| <b>Gearlube GL-5 85W-140</b> | <b>Unigear LS GL-3/GL-5 85W-140</b> |               |

*Change every 2000 hours/ 12 months*

| USE                      |                           | CLIMATE                     |
|--------------------------|---------------------------|-----------------------------|
| Normal                   |                           | Moderate                    |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2  | PRODUCT RECOMMENDATION 3    |
| <b>SP Gear 1011</b>      | <b>Syngear TDL 75W-90</b> | <b>Gearlube GL-5 80W-90</b> |

*Change every 2000 hours/ 12 months*

| USE                      |                          | CLIMATE |
|--------------------------|--------------------------|---------|
| Normal                   |                          | Arctic  |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |         |
| <b>SP Gear 5015</b>      | <b>SP Gear 1071</b>      |         |

*Change every 2000 hours/ 12 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.