

CATERPILLAR TRACKED EXCAVATORS

229 1GF (1986-1990)

**ENGINE**

Capacity: 13,3 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 2

Dieselfleet CD+ 15W-40

PRODUCT RECOMMENDATION 3

Multifleet SHPD 15W-40*Change every 250 hours/ 1 months***FINAL DRIVES**

Capacity: 53 liter

USE

Normal

CLIMATE

Mediterranean

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 50*Check every 1 months/ 250 hours*

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 30*Check every 1 months/ 250 hours*

USE

Normal

CLIMATE

Arctic

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 10W*Check every 1 months/ 250 hours***HYDRAULIC SYSTEM**

Capacity: 303 liter

USE

Normal

CLIMATE

Mediterranean

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 30*Check every 3 months/ 500 hours, change every 12 months/ 2000 hours*

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 10W*Check every 3 months/ 500 hours, change every 12 months/ 2000 hours*

CATERPILLAR TRACKED EXCAVATORS

229 1GF (1986-1990)



GREASE POINTS/NIPPLES

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

MoS2 Grease EP 2

COOLING SYSTEM

Capacity: 38 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 17*Change every 2000 hours/ 12 months*

SWING REDUCTION UNIT

Capacity: 28 liter

USE

Normal

CLIMATE

Mediterranean

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 50*Check every 1 months/ 250 hours*

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 30*Check every 1 months/ 250 hours*

USE

Normal

CLIMATE

Arctic

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 10W*Check every 1 months/ 250 hours*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.