

# CATERPILLAR TRACKED EXCAVATORS

## 245 84X (TILL 1990)

**ENGINE**

Capacity: 38-42 liter

**USE**

Normal

**CLIMATE**

Mediterranean

**PRODUCT RECOMMENDATION 1****Multifleet SCD 40****PRODUCT RECOMMENDATION 2****Multifleet SCD 30***Change every 250 hours/ 1 months***USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Kroontrak MTH 10W-30****PRODUCT RECOMMENDATION 2****Synfleet SHPD 10W-40****PRODUCT RECOMMENDATION 3****Dieselfleet CD+ 15W-40***Change every 250 hours/ 1 months***USE**

Normal

**CLIMATE**

Cold

**PRODUCT RECOMMENDATION 1****Multifleet SCD 10W***Change every 250 hours/ 1 months***FINAL DRIVES**

Capacity: 60 liter (each side)

**USE**

Normal

**CLIMATE**

Mediterranean

**PRODUCT RECOMMENDATION 1****Multifleet SCD 50****PRODUCT RECOMMENDATION 2****Multifleet SCD 40***Check every 1 months/ 250 hours***USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Multifleet SCD 30***Check every 1 months/ 250 hours***USE**

Normal

**CLIMATE**

Arctic

**PRODUCT RECOMMENDATION 1****Multifleet SCD 10W***Check every 1 months/ 250 hours*

# CATERPILLAR TRACKED EXCAVATORS

## 245 84X (TILL 1990)



### HYDRAULIC SYSTEM

Capacity: 403 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

**Gear Oil Alcat 30***Check every 3 months/ 500 hours, change every 12 months/ 2000 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gear Oil Alcat 10W***Check every 3 months/ 500 hours, change every 12 months/ 2000 hours*

### GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**MoS2 Grease EP 2**

### COOLING SYSTEM

Capacity: 87 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Coolant SP 17***Check every 1 months/ 250 hours, change every 12 months/ 2000 hours*

### PUMP DRIVE

Capacity: 6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Multifleet SCD 10W***Check every 50 hours, change every 12 months/ 2000 hours*

# CATERPILLAR TRACKED EXCAVATORS

## 245 84X (TILL 1990)



### SWING REDUCTION UNIT

Capacity: 35 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Multifleet SCD 50</b>	<b>Multifleet SCD 40</b>	

Check every 1 months/ 250 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Multifleet SCD 30</b>		

Check every 1 months/ 250 hours

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
<b>Multifleet SCD 10W</b>		

Check every 1 months/ 250 hours

### TRACK PINS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Multifleet SCD 30</b>		

### TRACK ROLLERS & IDLERS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Multifleet SCD 30</b>		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.