CATERPILLAR VIBRATORY COMPACTORS CB/CC/CD/CP/CS CS-533 3BL/4HL



ENGINE Caterpillar 3116 Capacity: 15,2 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 40	Multifleet SCD 30	
Check every 10 hours, change ever	y 1 months/ 250 hours	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40
Check every 10 hours, change ever	y 1 months/ 250 hours	
USE		CLIMATE
Normal		Cold

Check every 10 hours, change every 1 months/ 250 hours

DIFFERENTIAL Capacity: 16,1 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT
Check every 1 months/ 250 hours,	change every 12 months/ 2000 hours	'

TRANSFERBOX Capacity: 0,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT
Check every 1 months/ 250 hours,	change every 12 months/ 2000 hours	1

CATERPILLAR VIBRATORY COMPACTORS CB/CC/CD/CP/CS CS-533 3BL/4HL



HYDRAULIC SYSTEM Capacity: 117,5 liter (Hydraulic tank)			
USE		CLIMATE	
Normal		Mediterranean	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Multifleet SCD 40	Multifleet SCD 30		
Check every 10 hours, change every 2000 hours/ 12 months			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40	
Check every 10 hours, change every 2000 hours/ 12 months			
USE		CLIMATE	
Normal		Cold	
PRODUCT RECOMMENDATION 1			
Multifleet SCD 10W			
Check every 10 hours, change every 2000 hours/ 12 months			

GREASE POINTS/NIPPLES		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

COOLING SYSTEM Capacity: 37,9 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant SP 15+	Coolant SP 12		
Check every 10 hours, change eve	ury 24 months/ 2000 hours	,	

Check every 10 hours, change every 24 months/ 3000 hours

DRUM SUPPORT BEARING Capacity: 2,4 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Abacot MEP HD 220		
Check every 1 months/ 250 hours, change	e every 6 months/ 1000 hours	

CATERPILLAR VIBRATORY COMPACTORS CB/CC/CD/CP/CS CS-533 3BL/4HL



WEIGHT SHAFT BEARING Capacity: 55 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Abacot MEP HD 220		
Charle avant 1 manths/250 hours shangs	avany 6 mantha/ 1000 haura	

Check every 1 months/ 250 hours, change every 6 months/ 1000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.