CATERPILLAR VIBRATORY COMPACTORS CB/CC/CD/CP/CS CS-573 8PK



| ENGINE Caterpillar 3116 Capacity: 15,2 liter | | |
|--|-------------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Multifleet SCD 40 | Multifleet SCD 30 | |
| Check every 10 hours, change every 1 m | onths/ 250 hours | |
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agridiesel CRD+ 15W-40 | Kroontrak MTH 10W-30 | Synfleet SHPD 10W-40 |
| Check every 10 hours, change every 1 m | onths/ 250 hours | |
| USE | | CLIMATE |
| Normal | | Cold |
| PRODUCT RECOMMENDATION 1 | | |
| Multifleet SCD 10W | | |
| Check every 10 hours, change every 1 m | onths/ 250 hours | |
| | | |
| DIFFERENTIAL Capacity: 16,1 liter | | |
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Agrifluid HT | | |
| Check every 1 months/ 250 hours, chang | e every 12 months/ 2000 hours | |
| USE | | CLIMATE |
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |

Agrifluid HT

Change every 100 hours

CATERPILLAR VIBRATORY COMPACTORS CB/CC/CD/CP/CS CS-573 8PK



| TRANSFERBOX Capacity: 0,5 liter | | |
|---|-----------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Agrifluid HT | | |
| Check every 1 months/ 250 hours, change | every 12 months/ 2000 hours | |
| USE | | CLIMATE |
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Agrifluid HT | | |
| Change every 100 hours | | |

| HYDRAULIC SYSTEM Capacity: 132,6 liter (Hydraulic tank) | | |
|--|--------------------------|---------------|
| USE | | CLIMATE |
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Multifleet SCD 30 | Gear Oil Alcat 30 | |
| | | |

Check every 10 hours, change every 2000 hours/ 12 months

| Kroontrak MTH 10W-30 | Synfleet SHPD 10W-40 | Dieselfleet CD+ 15W-40 |
|--------------------------|--------------------------|--------------------------|
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Normal | | Moderate |
| USE | | CLIMATE |

Check every 10 hours, change every 2000 hours/ 12 months

| GREASE POINTS/NIPPLES | | |
|--------------------------|--|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| MoS2 Grease EP 2 | | |

| COOLING SYSTEM Capacity: 36,4 liter | | | |
|--|--------------------------|----------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| Coolant SP 15+ | Coolant SP 12 | | |
| Check every 10 hours, change every 24 | months/ 3000 hours | | |

CATERPILLAR VIBRATORY COMPACTORS CB/CC/CD/CP/CS CS-573 8PK



| DRUM SUPPORT BEARING Capacity: 2 liter | |
|---|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Abacot MEP HD 220 | |
| | |

Check every 1 months/ 250 hours, change every 6 months/ 1000 hours

| WEIGHT SHAFT BEARING Capacity: 49 liter | |
|--|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Abacot MEP HD 220 | |
| Check every 1 months/ 250 hours, change every 6 months/ 1000 hours | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.