

CLAAS TELESCOPIC HANDLERS

SCORPION 9055 DEUTZ TCD 4.1 L4 (2014 AND AFTER)



ENGINE Deutz TCD 4.1 L4
Capacity: 10,5 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Agrisynth LSP Ultra 10W-40

PRODUCT RECOMMENDATION 2

Agrisynth MSP 10W-40

PRODUCT RECOMMENDATION 3

Agridiesel MSP 15W-40

Change every 500 hours/ 12 months

DIFFERENTIAL FRONT
Capacity: 7,1 liter (each)

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90

DIFFERENTIAL REAR
Capacity: 7,1 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90

HUB REDUCTIONS FRONT
Capacity: 0,75 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90

HUB REDUCTIONS REAR
Capacity: 0,75 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90

CLAAS TELESCOPIC HANDLERS

SCORPION 9055 DEUTZ TCD 4.1 L4 (2014 AND AFTER)

**TRANSMISSION HYDROSTATIC** Varipower Plus

Capacity: 4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

HYDRAULIC SYSTEM

Capacity: 200 liter (Hydraulic system including tank), Capacity: 100 liter (Hydraulic tank)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus HCD 46		

Change every 1500 hours/ 12 months

USE		CLIMATE
Biodegradable oil		Moderate
PRODUCT RECOMMENDATION 1		
Perlus Biosynth 46		

*Change every 1500 hours/ 12 months***GREASE POINTS/NIPPLES**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

COOLING SYSTEM

Capacity: 23 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.