DENKA LIFT BOOM LIFTS DK DK8 JR12



HYDRAULIC SYSTEM Capacity: 20 liter (Hydraulic tank), Capacity: 25 liter (System)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 22		
Check every 2 weeks, change every	v 24 months	

GREASE POINTS/NIPPLES OTHERS

USE

Normal

PRODUCT RECOMMENDATION 1

PRODUCT RECOMMENDATION 2

PRODUCT RECOMMENDATION 3

Q5 MP Calcep Grease EP 2

Change every 2 weeks

Labora Grease

GREASE POINTS/NIPPLES SWING GEAR		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		
Change every 12 months		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

MP Lithep Grease EP 2